

Power Packed Resistors From

WIRE WOUND RESISTORS



CURRENT SENSE RESISTORS

HIA

Power Axial type.
Power Rating : 0.5W to 20W
Resistance Range : R01 to 120K
Tolerances Available : 10%, 5%, 3%, 1%
Features : • Flame retardant • Pulse type available. • Thermocoat precision power. • Non-inductive type available.

HFP

Power type PCB mounting.
Power Rating : 2W to 8W (at 70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%
Features : • Low cost • Automated assembly and wave soldering possible. • Commercial applications.

HSR

Capacitor discharge.
Wire wound symmetry resistors
Power Rating : 8.25W & 11W (70°C)
Resistance Range : 10K to 70K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Stainless steel mounting terminals for direct mounting on to capacitors.

HCA/HCV

Power Axial type
Power Rating : 1W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • High insulation. • Fire proof. • Resistant to aggressive solvents. • Pulse type available. • Bracket acts as heat sink.

OA / OP

Open Frame / Axial and PCB Mounting - Shunt Type.
Power Rating : 0.5W to 5W (85°C)
Resistance Range : R002 to R10
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Non insulated. • Surge / current sensing applications.

BR

Slim type Metal Plate / Preformed Resistance Strip.
Power Rating : 2W to 10W (70°C)
Resistance Range : R01 to 1R2
Tolerances Available : 10%, 5%
Features : • Radial configuration. • Negligible inductance. • Choice of 3 different preformings available.

RL

Alloy ribbon element in cylindrical ceramic body.
Axial type.
Power Rating : 0.5W to 10W (25°C)
Resistance Range : R002 to R80
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Negligible inductance. • Replaces moulded type.

FUSIBLE RESISTORS

(Safety Version)

FRS

Wire wound type.
Power Rating : 1W to 5W
Resistance Range : 10R to 3K3
Tolerances Available : 10%, 5%
Features : • Fire retardant coating. • UL requirements met satisfactorily. • Fail safe 'safety version' available.

HI-TECH RESISTORS PVT. LTD.

AN ISO TS 16949: 2009 CERTIFIED COMPANY
Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA.
Tel: +91-712-2531134, 2533269, 2553691. Fax: +91-712-2528334, 2556351.
e-mail: info@htr-india.com | www.htr-india.com



Metaphors

UNIVERSAL TESTER WITH LCR MEASUREMENT

MME-UT 20 is universal combo tester cum LCR Meter. It has 40 x 2 LCD, 24 keys Keypad, 20 pin ZIF for IC Testing and component bases for Inductance, Capacitance, Resistor, Transistor and Regulator.



- ♦ Tests Digital ICs TTL/CMOS (14/16/20 pin)
- ♦ Tests Linear / Analog ICs (4, 6, 8, 14, 20 Pins)
- ♦ Measures L, C, R with Calibration Facility
- ♦ μ C Development System
- ♦ Serial Port for upgradation.
- ♦ Tests Diode, Transistors, SCR, UJT, FET, Regulators, Displays

MME-UIT 40 Universal IC Tester with in-circuit IC Testing

MME-DIT 2040 Digital IC Tester

MME-ECT 20 Electronic Components Tester

MME-ADIT 40

MME-LICT 20

Analog & Digital IC Tester

Analog/Linear IC Tester

MME-DIT 20

MME-HDIT 20

20 Pin Digital IC Tester

Handheld Digital IC Tester

8085 μ P Kits

MME - 855
MICRO - 8085

8086 μ P Kits

TR 8086 with battery and RS 232 interface

8051 μ C Kits

MICRO - 8051
MAX-52 with assembler

ARM - 7 μ C Kits

LPC - 2148 based
32 bit ARM μ C Kit

Advanced..... Yet easy to use systems from



MINMAX ELECTRONICS

87/1, 1-A Cross, 5th Main,
Domlur II Stage, Bangalore-560 071
Phone : 080- 2535 3085 / 2535 2391
E-mail : minmax@vsnl.com
web : www.minmax.co.in