


## AC-DC LED Driver



|                                 | MIP5530MDSLJ           | MIP5540MSSCF                      |
|---------------------------------|------------------------|-----------------------------------|
| Package                         | TO-220PD7              | DIP7-A1                           |
| Drain Breakdown Voltage         | 700V                   | 400V                              |
| Power MOS ON state resistance   | 3.5Ω typ.              | 3.7Ω typ.                         |
| Power Factor Correction Circuit | Yes (PFC>0.9)          | Yes (PFC>0.9)                     |
| Dimmer function                 | Triac Dimmer           | Possible                          |
|                                 | PWM Dimmer             | Possible                          |
|                                 | Peak Current Limit     | 1.5A (Max)                        |
| Output current                  | Average current        | < 700mA                           |
|                                 |                        | (Possible by external adjustment) |
| Protections                     | Over Temp. Pro         | Over Temp. Pro.                   |
|                                 | LED short Pro          | LED short Pro.                    |
| Input Voltage                   | Non-isolated           | AC100V~240V                       |
|                                 | Isolated               | AC100V~240V                       |
| Power Supply Voltage            | Vin detection function | > DC20V                           |
|                                 | > DC24V                |                                   |




## LED Driver Solutions

Ideas for Light

| Part Number                 | AN30888A                              | AN30888B      |
|-----------------------------|---------------------------------------|---------------|
| Type of DCDC                | Buck, Boost, Buck-Boost               |               |
| Operating Input Voltage     | 3V to 20V                             | 3V to 15V     |
| Low standby current         | Lower than 10 μA                      |               |
| Operating Quiescent Current | Lower than 1 mA                       |               |
| Under-Voltage Lock Out      | 2.1V +/- 0.2V                         |               |
| Over Voltage Protection     | Externally configurable               |               |
| Dimming                     | a) Voltage Feedback [2 levels]        |               |
|                             | b) PWM Based (< 1 kHz)                |               |
| Efficiency                  | Up to 92%                             |               |
| Switching Frequency         | 1 MHz                                 |               |
| Output Current              | Up to Few Amperes [External N-MOSFET] |               |
| Output Boost Voltage        | Up to 35 V                            |               |
| LED Drive Capability        | Up to 10 Power LEDs in series         |               |
| Package                     | SSOP - 16 pins                        | QFN - 16 Pins |

## DC-DC LED Driver



Semiconductor Company, Panasonic Corporation

<http://www.semicon.panasonic.co.jp/en/>

For more information, please email us at [semicon.enquiry@sg.panasonic.com](mailto:semicon.enquiry@sg.panasonic.com)