

Low-voltage op-amps

Texas Instruments (TI) has expanded its 1.8V precision operational amplifier (op-amp) portfolio with a new line of op-amps for low-noise, high-impedance sensor measurement.

The first product in the OPAx320 family—the two-channel OPA2320—provides 20 MHz of gain bandwidth and 0.2pA input bias current to enable a very high accuracy and dynamic range for high-impedance optical and chemical sensor front-ends, programmable logic controllers, motor control loops, and test and measurement equipment.

The OPAx320 products offer a maximum input bias current of 0.9 pA to support high-impedance sensor signal conditioning and deliver precision with zero crossover distortion.

Texas Instruments (India) Pvt Ltd, Bengaluru

Fax: (080) 25048286

Phone: 25099221

Web: www.ti.com

Military analogue switches

Vishay Intertechnology, Inc. has expanded its family of MIL-PRF-38535-screened analogue switches and multiplexers with the release of the hi-rel DG408—an 8-channel, single-ended analogue multiplexer.



The MIL-PRF-38535 specification is a standard that establishes the performance, quality and reliability requirements for IC components used in systems being built for military and critical avionic applications.

Designed to connect one of eight inputs to a common output determined by a 3-bit binary address, the DG408 is optimised for high-speed data acquisition, audio signal routing, and battery-powered and remote

instrumentation. The device features a 44V maximum supply rating, low 'on' resistance of 100 ohms, and low charge injection of 20 pC. Its enable pin allows multiple devices to be used together to increase the number of input signals in an application.

Vishay Components India Pvt Ltd, Bengaluru

Fax: (080) 25584291

Phone: 25586277

E-mail: business-asia@Vishay.com

Motor-control ICs

Millennium Semiconductors has introduced high-performance, low-power motor-control ICs from Unisonic Technologies Corporation (UTC)—a strategy partner of LianShun Electronics in Taiwan. These ICs are priced com-



petitively and are available in various types such as single-phase, two-phase and three-phase. Features include seven-segment decoder display drivers, a reference clock, and frequency and clock display driver.

The ICs have an inbuilt Hall amplifier and hall bias circuit and internal pulse-width modulation (PWM) control. These can be used to drive DC, stepper and brushless DC motors in such applications as radio cassette tape recorders, DC fans and hard disk drives.

Millennium Semiconductors, Pune

Phone: (020)27484800

E-mail: sunil@millenniumsemi.com,

tech4@millenniumsemi.com

Electronic current limiters

Bourns has introduced its latest series of TBU (transient blocking unit) circuit-protection devices for high-speed protection of communication ports. These devices are claimed to be the industry's first electronic current limiters that tolerate AC mains power contact without circuit damage.



Designated the Bourns TBU DT-series, the new circuit-protection devices provide protection against faults caused by short circuits, AC power cross, induction and lightning surges. The series features eight models and offers continuous AC voltage ratings up to 425Vrms and nominal trigger currents ranging from 150 mA to 750 mA. The devices come in a surface-mount DFN package and are lead-free and RoHS-compliant.

Bourns Asia Pacific, Inc., Taiwan

Fax: +(886) 25624116

Phone: 25624117

E-mail: josephine.chen@bourns.com

Web: www.bourns.com

TEST & MEASUREMENT

Pulse/function/arbitrary noise generator

Agilent Technologies Inc. has expanded its pulse/function/arbitrary-noise waveform generator family with the launch of the 81160A. The new waveform generator helps R&D and test engineers test higher-speed, higher-bandwidth analogue, digital and



mixed-signal devices more efficiently and with greater precision.

The 81160A eliminates the need for cumbersome multi-instrument setups for stress testing devices. It provides versatile waveforms along with superior signals with an intrinsic jitter of 7ps rms which helps engineers define better performance specifications for their devices.

It is ideal for general-purpose bench tests and advanced serial data stress tests as it can generate 330MHz pulses and 500MHz function/arbitrary