

Power Packed Resistors From

WIRE WOUND RESISTORS



CURRENT SENSE RESISTORS

HMV

Flat Vertical Mounting Type.
Power Rating: 2.5W To 15W (70°C)
Resistance Range: R10 To 36k
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features: • Ceramic Legs Act As Heat Sink.
• Slim Profile. • Space Saver.
• Pulse Type Available.
Available In Low Ohm Current Sense Type As Hmv1 Series.



HSV

Vertical Mounting.
Encased with Slots for Mounting Support.
Power Rating: 4W To 17W (70°C)
Resistance Range: R04 To 82k
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features: • Designed For Colour TV Application.
• Suitable For High Density PCB's.
• Vertical Mounting Pillar Supports Available.
• Pulse Type Available.



HFP

Power Type PCB Mounting.
Power Rating: 2.5W To 8W (at 70°C)
Resistance Range: R10 To 56k
Tolerances Available: 10%, 5%
Features: • Low Cost.
• Automated Assembly
and Wave Soldering Possible.
• Commercial Applications.



HIA

Power Axial Type.
Power Rating: 0.5W To 20W
Resistance Range: R01 To 120k
Tolerances Available: 10%, 5%, 3%, 1%
Features: • Flame Retardant
• Thermocast Precision Power
• Pulse Type Available.
• Non-inductive Type Available.



OA / OP

Open Frame / Axial and
PCB Mounting - Shunt Type.
Power Rating: 0.5W To 5W (85°C)
Resistance Range: R002 To R10
Tolerances Available:
10%, 5%, 3%, 2%, 1%
Features: • Non Insulated.
• Surge / Current Sensing Applications.



RL

Alloy Ribbon Element in Cylindrical
Ceramic Body. Axial Type.
Power Rating: 0.5W To 10W (25°C)
Resistance Range: R002 To R80
Tolerances Available:
10%, 5%, 3%, 2%, 1%, 0.5%
Features: • Negligible Inductance
• Replaces Moulded Type.



BR

Sim Type Metal Plate.
Preformed Resistance Strip.
Power Rating: 2W To 10W (70°C)
Resistance Range: R01 To 1k2
Tolerances Available: 10%, 5%
Features: • Radial Configuration.
• Negligible Inductance. • Choice
of 3 Different Preformings Available.



OFSC

PCB Mounting.
Power Rating:
5W & 10W (70°C)
Resistance Range:
R00012 To R003
Tolerances Available:
5%, 3%, 2%, 1.5%, 1%
Features: • Silicone coated.
• Surge / Current Sensing Applications.
• Negligible Inductance.



HI-TECH RESISTORS PVT. LTD.

AN ISO/TS 16949:2009 CERTIFIED COMPANY

Buty Compound, Mount Road Extension, Nagpur-440 001. INDIA Tel.: +91-712-2531134, 2533269, 2553691.
Fax: +91-712-2528334, 2556351. e-mail: info@htr-india.com | www.htr-india.com

Mumbai



SMD
ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE
& PASSIVE COMPONENTS

Authorised Distributor



SMD E-Capacitors



SMD Transistors
SMD LED SMD Diodes
SMD Capacitors



SMD Resistors



CHIP TRANSISTORS / CHIP DIODES / CHIP LED'S / CHIP CAPACITORS / CHIP IC's

- | | | |
|--------------------------------|--------------------------------------|---------------------------|
| • CHIP RESISTORS | • CHIP BRIDGE RECTIFIERS | • CHIP FERRITE BEADS |
| • CHIP RESISTOR NETWORKS | • CHIP TRANSIENT VOLTAGE SUPPRESSORS | • CHIP HALL SENSORS |
| • CHIP CAPACITORS | • CHIP IN LED'S & SENSORS | • CHIP POTENTIOMETERS |
| • CHIP TANTALUM CAPACITORS | • CHIP IC'S | • CHIP FUSES |
| • CHIP ELECTROLYTIC CAPACITORS | • CHIP MOSFETS | • CHIP SWITCH |
| • CHIP ZENERS & DIODES | • CHIP REGULATORS | • CHIP MOV'S |
| • CHIP TRANSISTORS | • CHIP OPTO COUPLERS | • CHIP THERMISTORS |
| • CHIP LED'S | • CHIP TRIMMER CAPACITORS | • CHIP SOLDER PASTE |
| • CHIP SCHOTTKY DIODES | • CHIP INDUCTORS | • CHIP SOLDER WIRE 26 SWG |



54-C, Jyoti Estate, Proctor Road, Near Parijat Bldg., Off. Lammington Road,
Mumbai - 400 007. INDIA. Tel.: 91-22-3240 2444 • Mob.: 93242 11912

E-mail: smedelectro@vsnl.net

STOCKIST OF ELECTRONIC COMPONENTS



Circuit Electro-Components Pvt. Ltd.



"Drug House", Bldg. 54-B, Proctor Road, Mumbai - 7, INDIA.
Pin Code: 400 007 • Tel.: 2387 7777 / 2380 8888
Mob.: 93222 24570 / 93222 81112 • Fax: 91-22-2387 9335
E-mail: circuit@vsnl.com • Website: www.cirkitellectro.com

