

WIRE WOUND RESISTORS



CURRENT SENSE RESISTORS

HCP

Power Type
PCB Mounting
Power Rating: 3W to 20W (70°C)
Resistance Range: R10 to 56K
Tolerances Available: 10%, 5%
Features: • Inverter / Power Supply applications
• Adaptable to automated assembly
• Choice of terminal stand-off heights
• Choice of terminals to suit exact PCB requirements



HCL

Hi Power Lug
Terminations
Bracket Mounting
Power Rating: 10W to 40W (70°C)
Resistance Range: R10 to 68K
Tolerances Available: 10%, 5%
Features: • Low Surface Temperature
• Replaces Old Radial Style
• Compatible With AMP F187 & AMP 250
• Low Surface Temperature
• Replaces Old Radial Style
• Compatible With AMP F187 & AMP 250 Connectors
• Pulse Type Available



HMV

Flat Vertical Mounting Type
Power Rating: 2.5W to 15W (70°C)
Resistance Range: R10 to 36K
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features: • Ceramic Legs Act As Heat Sink
• Slim Profile • Space Saver
• Pulse Type Available
Available In Low Ohm Current Sense Type As HMVL Series.



HEA

Semi Precision Axial Type
Power Rating: 2.5W to 17W (70°C)
Resistance Range: R025 to 70K
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features: • Low Surface Temperature
• Fire Retardant • Pulse Type Available



OA / OP

Open Frame / Axial and PCB Mounting - Shunt Type
Power Rating: 0.5W to 5W (85°C)
Resistance Range: R002 to R10
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features: • Non Insulated
• Surge / Current Sensing Applications



HEAL

Alloy Ribbon Element / Axial Type
Square Profile Ceramic Tube
Power Rating: 2.5W to 12W (70°C)
Resistance Range: R0025 to R20
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features: • Negligible Inductance
• Surge / Current Sensing Applications



OF

Open Frame
PCB Mounting
Punched Out Style
Power Rating: 1W to 10W (85°C)
Resistance Range: R0005 to R068
Tolerances Available: 10%, 5%, 3%, 2%, 1%
Features: • Low TCR
• Tailor-made Solutions Possible



OFSC

PCB Mounting
Power Rating: 5W & 10W (70°C)
Resistance Range: R00012 to R003
Tolerances Available: 5%, 3%, 2%, 1.5%, 1%
Features: • Silicone coated
• Surge / Current Sensing Applications
• Negligible inductance



HI-TECH RESISTORS PVT. LTD.

AN ISO/TS 16949:2009 CERTIFIED COMPANY

Bully Compound, Mount Road Extension, Nagpur-440 001, INDIA.
Tel: +91-712-2531134, 2533269, 2533691. Fax: +91-712-2528334, 2556351.
e-mail: info@htr-india.com | www.htr-india.com



Memorandum



SMD
ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE & PASSIVE COMPONENTS

Authorised Distributor



CHIP TRANSISTORS / CHIP DIODES / CHIP LED's / CHIP CAPACITORS / CHIP IC's

- | | | |
|--------------------------------|--------------------------------------|----------------------------|
| • CHIP RESISTORS | • CHIP BRIDGE RECTIFIERS | • CHIP FERRITE BEADS |
| • CHIP RESISTOR NETWORKS | • CHIP TRANSIENT VOLTAGE SUPPRESSORS | • CHIP HALL SENSORS |
| • CHIP CAPACITORS | • CHIP IC'S | • CHIP IN LEADS & SENSORS |
| • CHIP TANTALUM CAPACITORS | • CHIP MOSFETS | • CHIP POTENTIOMETERS |
| • CHIP ELECTROLYTIC CAPACITORS | • CHIP REGULATORS | • CHIP FUSES |
| • CHIP ZENERS & DIODES | • CHIP OPTO COUPLERS | • CHIP SWITCH |
| • CHIP TRANSISTORS | • CHIP TRIMMER CAPACITORS | • CHIP MOV'S |
| • CHIP LED'S | • CHIP INDUCTORS | • CHIP THERMISTORS |
| • CHIP SCHOTTKY DIODES | | • CHIP SOLDER PASTE |
| | | • CHIP SOLDER WIRE 28 SWG. |



54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road, Mumbai - 400 007, INDIA. Tel: 91-22-3240 2444 • Mob: 93242 11912

E-mail: smdelectro@vsnl.net

STOCKIST OF ELECTRONIC COMPONENTS



Circuit Electro-Components Pvt. Ltd.



"Dragon House", Bldg. 54-B, Proctor Road, Mumbai - 7, INDIA.
Pin Code: 400 007 • Tel: 2367 7777 / 2368 6888
Mob: 93222 34370 / 93227 91112 • Fax: 91-22-2367 9335
E-mail: circuit@vsnl.com • Website: www.circuitindia.com

MOODS GENVAL AVAILABLE