

uses 'set' and 'get' methods. Hence the date parameters can be sent directly into the Date() function, modifying the contents of the calendar table dynamically, without changing the system parameters. The initial program output is shown in Screenshot 1.

The current or live date is shown in green colour (refer Screenshot 2).

The calendar is programmed to display holidays in pink colour and event dates in blue colour for easy recognition (refer Screenshots 3 and 4). These colours can be modified in the source code as and when desired by the user.

Function descriptions. The main function that drives this program is the Show() function, which gets the data from JavaScript's built-in Date() function. It extracts year and month details and arranges the dates for a particular month. A predefined array contains the names of the months, as the function only returns numbers 0-11 for January-December, respectively, then arranges numbers from 1 to 31/30/29/28 as per the

month and year selected by you.

Other auxiliary functions include PreMn() to display previous month, NxtMn() to display next month, PreYr() for previous year and NxtYr() for next year. Today() function is used to return to the current date, month and year. If the year goes below 70 AD or above 15,000 AD, 'NaN' (not a number) text fills in the calendar grid on the screen. So the year to be displayed should be between 70 AD and 15,000 AD in this program.

Cascaded style sheets. This JavaScript program uses HTML pages for running. JavaScript function requires HTML buttons, table elements and many such tags to display the program as per the requirements. Cascaded style sheets (CSS) are used to enhance the display of the program by bringing in rich colours and good formatting. In-program CSS using the <style> element tag is implemented to change and enhance the appearance of the program.

CSS are of three types: external,

internal and inline.

External CSS are written as separate entities and then saved with extension 'css'. These are then called by the main program as <style src='sample.css'></style>

Internal CSS are defined within the main program under <style></style> tags and are called into the required elements by using class parameter.

Inline CSS are defined within the elemental tag, which can change only the appearance of the tag that declares this. For example, the code "<p style='color:blue;margin-left:20px'>EFY Enterprises Pvt Ltd.</p>" will display "EFY Enterprises Pvt Ltd." text in blue colour.

Internal and inline CSS styles are used in this program.

EFY note. The source code of this article is available on www.efymag.com website.

The author is a B.Tech in electronics and communications engineering, likes coding JavaScript and has keen interest in space technology (satellite communication) and mobile communication

NAVI CAL.HTM

```
<html>
<head>
<title>JavaScript based Navigational
Calendar Interface</title>
<meta http-equiv="Page-Enter" content="r
ewalTrans(Duration=5.0,Transition=23)">
<meta http-equiv="Page-Enter" content="
blendTrans(Duration=3.0)">
<meta http-equiv="Page-Exit" content="r
ewalTrans(Duration=5.0,Transition=23)">
<style>
.C
{
border:1;
color:Cyan;
background:Midnightblue;
font-family:Constantia;
font-size:20;
font-weight:regular;
text-align:center;
cursor:hand;
width:80;
height:80;
overflow:hidden;
}
.O
{
border:1;
color:Yellow;
background:Midnightblue;
font-family:Constantia;
font-size:20;
font-weight:regular;
text-align:center;

```

```
cursor:hand;
width:80;
height:80;
overflow:hidden;
}
</style>
<script style="color:Red">This Application Requires JavaScript Plug-in which has to be initialized or installed. It seems that your OS does not have the Plug-in. Installed or has been disabled by you. Please Enable/Install the Plug-in. If you have the plug-in and is currently disabled, right-click on the light-yellow bar above, Choose "Allow Blocked Content..." and then click "Yes" from the consecutive dialog box, you should see the Application running, or else install the plug-in from Internet/Reliable Disc.</script>
<script language=JavaScript>
var dtst=new Date();
function Today()
```

```
{
dtst=new Date();Show();
}
function PreMn()
{
dtst.setDate(1);
var mn=dtst.getMonth();
while(mn=dtst.getMonth()){dtst.setMil-
liseconds(-86400000);}
Show();
}
function NxtMn()
{
dtst.setDate(28);
var mn=dtst.getMonth();
while(mn=dtst.getMonth()){dtst.setMil-
liseconds(86400000);}
Show();
}
function PreYr()
{
dtst.setFullYear(dtst.getFullYear()-
1);Show();
}
function NxtYr()
{
dtst.setFullYear(dtst.getFullYear()+1);Show();
}
function Show()
{
var td=new Date();
dtst.setDate(1);
var yr=dtst.getFullYear();
```