

New Products

COMPONENTS

Cortex processor-based microcontrollers

STMicroelectronics has introduced STM32 F4 series of Cortex-M processor-based microcontrollers. This extension to the STM32 platform is based on ARM Cortex-M4 core. The microcontrollers offer 210 DMIPS and 363 Coremark score.



The series operates at 168MHz frequency, and has single-cycle DSP instruction support, a floating-point unit, 192kB SRAM, embedded flash memory of 512 kB to 1 MB, and peripherals for imaging, connectivity and encryption. The series also offers up to fifteen communication interfaces including six USARTs running at up to 10.5 Mbps, three SPI running at up to 42 Mbps, three PC, two CAN and an SDIO.

STMicroelectronics Pvt Ltd, Greater Noida

Tax: (0120) 4243417

Phone: 4003001

E-mail: www.st.com

Web: www.st.com

LED driver ICs

Infineon Technologies has extended its family of switch-mode LED drivers for high-power LEDs used in general lighting applications. The



ICs combine thermal protection feature with output current ranging from 350 mA up to multiple amperes.

The ILD series includes LED driver ICs with integrated power stage as

well as external MOSFET. Input voltage is 4.5V to 42V for ILD4001, and 4.5V to 40V for ILD4035 and ILD4120. Dimming can be implemented using pulse-width modulation managed by a microcontroller or by analogue control voltage.

Arihant Electricals, New Delhi


Fax: (011) 23273554

Phone: 47637336

Web: www.infineon.com

Low-pin-count chip

Fujitsu Semiconductor has enhanced the lineup of 8-bit FMC-8FX microcontroller family with the addition of eight models of MB95630 series. The



products employ a DC brushless motor controller, an analogue voltage comparator, C-R oscillation circuit, voltage detection circuit as well as monitor timer circuit.

The chips have a low pin-count (32 pins), eight levels of power-saving mode and embedded single-wire on-chip debug module.

Fujitsu Semiconductor Asia Pte Ltd,

Bengaluru

Fax: (080) 28416660

Phone: 28419990

Web: www.fujitsu.com

Single-chip microcontroller

Renesas Electronics has introduced a 16-bit microcontroller for single-phase static electricity meters. The 78K0R/LG3-M has a 20MHz, 16-bit core with 128kB flash memory and 7kB RAM.



The microcontroller integrates a dedicated electrical power calculation circuit, an LCD driver circuit and a real-time clock with an independent power supply.

It also has an on-chip DSP metrology engine with four second-order precision Sigma Delta 24-bit analogue-to-digital converters (ADCs), and a two-channel 10-bit successive approximation ADC.

Renesas Electronics Singapore Pte Ltd,

Bengaluru

Fax: (080) 67208777

Phone: 67208700

Web: www.renesas.com

8-bit PIC microcontrollers

Microchip Technology has launched 8-bit PIC microcontrollers featuring configurable logic and peripheral integration in 6- to 20-pin packages.

The PIC10F(LF)32X and PIC1X(LF)150X incorporate new



peripherals including configurable logic cells, complementary waveform generators and numerically-controlled oscillators. These consume less power with currents of less than 30 μ A/MHz in active mode and less than 20 nA in sleep mode. Also, there is an on-chip 16MHz internal oscillator, analogue-