

tery from externally mounted box on the pole. Also, there is a provision to connect a large tubular lead-acid battery outside the LED fixture. The solar PV panel can be mounted on top of the light fixture or separately on top of the pole.



The built-in charging arrangement switches to grid power in case solar charging is not possible or insufficient due to adverse weather conditions. Solar charging is checked every 15 minutes to ascertain that the power is sufficient. Another monitoring circuit detects whether the battery is fully charged and if so, it switches to trickle charge with green LED flashing.

Darburi Green Energy Systems Ltd, New Delhi

E-mail: info@solarplanet.net
Web: www.solarplanet.in

COMPUTING

Development platform

iWave Systems Technologies has launched the i.MX508 quick-start board (QSB) around Freescale Semi-



conductor's i.MX508 processor and iWave's fifth i.MX-based design. The i.MX508 processor is a system-on-chip designed specifically for eReaders that incorporate a high-performance 800MHz ARM Cortex-A8 processor and an integrated hardware electronic paper display controller certified by E Ink to drive the Pearl panels.

The board offers an on-chip electronic paper display/LCD controller, Ethernet, dual USB, dual SD, micro USB device, VGA out, audio in/out and serial interfaces.

iWave Systems Technologies Pvt Ltd, Bengaluru
Phone: (080) 26781643

Network admin tools

Buffalo Technology has released Network Admin Tools v.1.3 to enable centralised management of multiple TeraStation network-attached storage (NAS) devices and offer file server experience coupled with domain integration.

Backward-compatible across RAID-enabled Buffalo TeraStation NAS systems, this NAS management software enables monitoring of alerts, schedule management for automatic configuration backup and firmware update, restoration of NAS settings, network mapping, and device configuration.

The software supports up to 300 storage devices with IP address.

Buffalo Inc., New Delhi

Fax: (011) 41538069

Phone: 41538059

E-mail: info-india@melcoinc.co.jp

Web: www.buffalo-asia.com

Industrial modular PATA SSD

Apacer Technology has rolled out an industrial modular PATA SSD for embedded/thin client devices. The ADM 4 (ATA disk module) adopts a 44-pin



connector and can be used either in parallel (at 180°) or perpendicularly (at 90° or 270°) for various mechanisms.

The modular SSD has read/write speed of 80/50 MB per second and is available in capacities of 1 GB to 16 GB. It has a single-level-cell chip and is designed to operate at extreme temperatures (-40°C to 85°C).

Vardhaman Technology Pvt Ltd, Mumbai

Fax: (022) 25007502

Phone: 25007002, 25007502

Web: in.apacer.com

TOOLS & EQUIPMENT

Desoldering system

OK International has released a shop air desoldering system. The MFR-



1150 along with the company's MFR-UK5 upgrade kit enables assemblers to transform

existing MFR systems into shop air desoldering systems.

The system has a built-in power supply, venturi workstand and desoldering hand-piece – that can be used in either a pencil-style or pistol-grip configuration. The venturi provides vacuum suction force of 56cm (25-inch) Hg or 0.85 bar.

OK International

Division of Dover India Pvt Ltd, Mumbai

E-mail: drame@okininternational.com

Web: www.okinternational.com

Nozzle cleaner

Kyoritsu Automation has launched the Eco SMT nozzle cleaner. The cleaner employs an automatic cleaning sequence and indexing system which includes an integrated drier unit as standard.

It features a programmable logic controller with touchscreen control, which allows programming of nozzle-cycle cleaning processes; with up to twelve nozzles cleaned and processed.



Cleaning and drying are programmed in sequence and can be independent. The height of the cleaning-

spray nozzle and the air-blower nozzle is adjustable, while loading and unloading can be done through sliding rather than plugging-in.

Kyoritsu Automation India Pvt Ltd, Thane

Phone: (0250) 2024668, 2471678

E-mail: sales@kyoritsuautomation.com

Web: www.kyoritsuautomation.com