APLUS SPEECH MELODY RF IC & MODULE

LOW COST VOICE OTP IC DURATION 10 SECONDS TO 180 MINUTES

Re-recordable Voice Ic 10 seconds to 16 minutes

VOICE OTP PROGRAMMING TOOL AVAILABLE

Mantra & Shloka IC COB
Custom Designed Speech Voice Melody Ic-COB-KIT Available.

STUDENT KITS, ENGG. KITS & PROJECTS

PIR Sensor, Ic & COB For Sound Effect, Waterfall, Doorbell, Clock, Alarm,

RF MODULES TX - RX - TR ASK - FSK - AV

Led Flasher, MCU with Speech & Melody, Custom Design Asic etc.

S.M. SEMICONDUCTORS

Ground Floor Bakul Baug, Vasundhara, Opp. Indian Bank, S.V. Road, Santacruz (West), Mumbai - 400 054

Tel. : 022-2618 2082 / 2617 3575 Fax : 91-22-26118035
Mobile : 9833374818 Website : www.aplusindia.net
E-mail : sales@aplusindia.net / sms003@sms003.com

STEAD®

ISO 9001:2008 CERTIFIED

Industrial Loads
Range : 1KW - 300KW

Resistors Aluminium Housed
Range : 0.1 ohms - 100 K ohms
Power : 5W - 1000 W
Tolerance : ±5%

Low Ohmic Power Resistors
Open Frame Axial & PCB Mounting
Range : 0.001 - 1 ohms Power : 0.5 W - 3 W
Tolerance : ±5%, ±2%, ±1%

Dynamic Breaking Resistor
Range : E1 - 100 K
Power : 40 W - 10000 W
Tolerance : ±5%

Resistors Adjustable / Fixed (Silicone Coated)
Range : E 001 - 500 K Power : 0.5 W - 5000 W
Tolerance : ±5%, ±2%, ±1%.

Rheostat (Open / Covered / LSM)
Range : 0.5 ohms - 10000 ohms
Power : 0.1 Amp - 200 Amp

Resistors Ceramic Encased
Range : E 001 - 100 K
Power : 3 W - 50 W
Tolerance : ±5%

Potentiometer (Single / Gang Type)
Range : 1 ohms - 10 K ohms
Power : 25 W - 1000 W
Tolerance : ±5%

STEAD ELECTRONICS (INDIA) PVT. LTD.

Sales Office : 1661/20, Mangal Market, Bhagirath Palace, Delhi-110006
Ph. : 23865929, 23862576 Fax : 011-23867465
Regd. Office : 17 U.A. Jawahar Nagar, Delhi-7
e-mail : sales@steadresistors.com visit at www.steadresistors.com

Power to Perform

- UPS
- INVERTERS
- BATTERIES

HEAT SEALED BATTERIES

BEACON

ISO CERTIFIED COMPANY

Tel.:0484-2460594, 0484-6465051, E-mail : beaconps@gmail.com
www.beaconpower.in

amplify your electronics

Friendly ARM 9 Boards

Available Range
Mini 2440 + 3.5" LCD
Mini 2440 + 7" LCD
Mini 2440 + VGA
Micro 2440 + 3.5" LCD
Micro 2440 + 7" LCD
Micro 2440 + VGA

Interface Modules
SPI CMOS Camera
USB Camera
USB Wifi Module
GSM / GPRS
Biometric Module
All Range of Sensor's

****Introducing 10.4" & 12.1" LCD**

FEATURES
CPU: 400 MHz Samsung 2440A ARM920T, RAM: 64 MB SDRAM, 32 bit 100 MHz Bus, Display Interface: 3.5", 7", VGA, Flash : 128MB(256MB) USB NAND Flash & 2 MB NOR Flash, OS Support : Linux 2.6, Windows CE, Android*
User Outputs: 4x LEDS, Keypad, SERIAL, USB, SD Card, Ethernet, Audio, EEPROM
**** Technical Support Provided & We do also undertake project development**

PDS
Port. Digital Storage Oscilloscope
(25~100 MHz Bandwidth)
Large 8" Screen for clear view
Battery Operation available

MSO

HDS-N
Hand Held Digi. Storage Oscilloscope
(25~100 MHz Bandwidth), 1 - 2 channel
3.8" TFT Screen for clear view
2 in1 (MultimeterFunction Support)

www.owon.co.in

AT UNBELIEVABLE PRICE

To amplify yourself with NEXT GENERATION ROBOTICS KITS

AMP TRONICS

amplify your electronics

6-3-905/B2, Jaffer Alibagh, Somajiguda, Hyderabad - 82. Ph.: +91 40 23302040, +91 9440122805
www.amp-tronics.com, www.owon.co.in E-mail : info@amp-tronics.com

DEALERS / DISTRIBUTORS ENQUIRIES SOLICITED