

they are well-suited for use in test and measurement and communications equipment.



Rotational life for both the models is 50k cycles with contact resistance at 100 milli-ohms for Model 54 and 30 milli-ohms for Model 56.

O/E/N, Vyttyla, Kerala

Fax: (0484) 2302211, 2302287

Phone: 2302483, 2301132, 2303709

Web: www.bourns.com

High-density connectors

HARTING has introduced high-density connectors for AV multimedia, theatre and concert installations. The Han Modular series inserts allow event installers to create high-density connectivity and cabling solutions with total signal handling flexibility, e.g., audio, video, communications, data and power, through different rugged IP 65/67 hoods and housings suitable for harsh handling conditions.

Multi-pin modules can support analogue and digital audio transfer. Multi-way coax modules can handle CCTV, SDI, HD-SDI and 3G-SDI video. A range of power modules allows current handling from a few amps up to 200 amps. Signal security between power and data lines can be assured through EMC screening options or SC fibre-optic modules.

HARTING India Pvt Ltd, Chennai

Fax: (044) 43560417

Phone: 43560415/416

E-mail: www.harting.in

Web: www.harting.com

POWER SUPPLY

Solar controllers

Morningstar has introduced a maximum power-point tracking (MPPT) battery charger for off-grid photovoltaic (PV) systems up to 3 kW. The controller is said to provide the industry's highest peak efficiency of 99 per cent and significantly less power loss compared to other MPPT controllers. It comes in two models—TS-MPPT-45 and TS-MPPT-60—with maximum battery current of 45 and 60 amps, respectively.

The solar controller uses a tracking algorithm that finds the solar array's peak power point with fast sweeping of the entire I-V curve. It includes on-board Ethernet for a Web-enabled interface and can log up to 200 days of data.

Avante Global Services Pvt Ltd, New Delhi

Fax: (011) 26473068

Phone: 26443097, 26233259, 26473069

E-mail: pg@avante.in, info@morningstarcorp.com

com

Web: www.ags.co.in, www.morningstarcorp.com

Power supply for LED lighting

Emerson Network Power has added a 25-watt series to its portfolio of power supplies for LED lighting.



The LDS25 series offers an input range of 120 to 277V AC and can deliver up to 700 mA at 36V DC. Constant-current mode operates from 36V down to 26V, while con-

stant-voltage mode operates with load currents from 300 to 700 mA or to the programmed current-limit level—which can be set by a single resistor to any value within this range. Alternatively, the output current can be user-adjusted over its full 0-700mA range by an IEC 60929-compliant dimming function, controlled by a 0-10V signal.

Nextech Electronics, Bengaluru

Fax: (080) 26608914

Phone: 4 205095/96

Web: www.EmersonNetworkPower.com

TOOLS & EQUIPMENT

Infrared IC heater

Amp Tronics has launched a microprocessor-controlled reflow oven that can be used for soldering various SMD and BGA components.



The 43×37×36cm³ T962A has maximum soldering area of 300×320 mm². Parameters of eight soldering cycles are pre-defined and the entire soldering process can be completed automatically from pre-heat, soak and reflow through to cool down.

Amp Tronics, Hyderabad

Phone: (040) 23320240

E-mail: info@amp-tronics.com

Laser-line alignment tool

P.G. Electronics has introduced a laser alignment device for locations where contactless centering of wound batches or stacks is to be aligned or monitored.

Type ELLD 101 is a visible laser-line unit with intensity control. Further, if the line-length and distance from projection to the job are known, the unit can be manufactured ac-