


cordingly. Suitable for operation off 15-24V DC, it is available in tubular



Laser Alignment Device



shape with fixing nut and clamp.

P.G. Electronics, Mumbai

Fax: (022) 66943788

Phone: 26763587, 26763831

E-mail: pgelec1981@yahoo.co.in, pgelectron-

ics@mtnl.net.in

Web: www.pgelectronics.iponline.com

LIGHTING

LED downlight

GlacialLight has expanded its Capella Series of LED products with the addition of GL-DL08 LED down-



light. The 20cm (8-inch) 18-watt LED downlight is an all-in-one bulb and fixture that provides 120 degrees of light.

The downlight comes in WW, NW and CW models with colour temperatures of 3000K, 4000K and 6000K, providing 830, 950, and 1200 lumens of light, respectively.

The downlights measure 240x13 mm² in size and have luminous efficacy of 46, 53 and 67 lumens per watt, offer CRI of up to 75 and accept a range of power sources from 100 to 240VAC.

Lotus Insulation Services, Pune

E-mail: sales@lotusin.co.in

Web: www.GlacialLight.com

Retrofit PowerLED GLS bulbs

Binay Opto has come up with Power LED bulbs in retrofit replacements for

40W, 50W and 60W general lighting service (GLS) bulbs. Similar in form factor to standard GLS bulbs, these feature a multiple-LED circuit design and are housed in rugged, extruded aluminium.



The PowerLED bulbs have a wide operating voltage range of 170-250V AC and are available in high-visibility scotopically enhanced cool daylight white or warm white colours.

Binay Opto Electronics Pvt Ltd, Kolkata

Fax: (033) 22421493

Phone: 22429082, 22103807

E-mail: info@binayled.com, binay@vsnl.com

TEST & MEASUREMENT

Digital storage oscilloscopes

Good Will Instruments has launched the GDS-1000A-U digital storage oscilloscope series.

The general-purpose, two-channel series includes 150MHz, 100MHz and 70MHz models having a real-time



sampling rate of 1 GSa/s and 2M point record length. Utilising MemoryPrime technology, the scopes are able to acquire single-shot and fast-varying waveforms. These have a 14cm (5.7-inch) colour TFT display, user-friendly human interface and USB device and host ports.

Good Will Instruments Co. Ltd

E-mail: india_marketing@goodwill.com.tw,

marketing@goodwill.com.tw

Web: www.gwinstek.com

Signal and spectrum analyser

Rohde & Schwarz has introduced an FSW signal and spectrum analyser in

three models that cover 2Hz to 8GHz, 13GHz and 26.5GHz frequency ranges. These analysers have a 31cm (12.1-inch) touchscreen and MultiView function.

At 10kHz carrier offset, the analyser achieves a phase-noise specification of less than -137 dBc (1 Hz).



It offers an analysis bandwidth of up to 160 MHz. Equipped with the R&S FSW-K6 option, the analyser also supports comprehensive analysis of pulsed signals.

Rohde & Schwarz India Pvt Ltd, New Delhi

Fax: (011) 42535433

Phone: 42535400

E-mail: sales.rsindia@rohde-schwarz.com

Web: www.rohde-schwarz.co.in

MISCELLANEOUS

Industrial SD card

Apacer has come up with an industrial embedded SD card designed for harsh storage environments. Compliant with Version 2.0 and SDHC Class 10 high-speed transmission standards, the card supports



SD and SPI modes. It is available in 256MB to 8GB capacities and offers sequential read and write speeds of up to 20 and 13 MB per second, respectively.

Apacer Technologies Pvt Ltd, Bengaluru

Phone: (080) 4152906/162/63

E-mail: india_sales@apacer.com