

APLUS SPEECH MELODY RF IC & MODULE

**LOW COST VOICE OTP IC DURATION
10 SECONDS TO 180 MINUTES**

Re-recordable Voice Ic 10 seconds to 16 minutes

VOICE OTP PROGRAMMING TOOL AVAILABLE

**Mantra & Shloka IC COB
Custom Designed Speech Voice
Melody Ic-COB-KIT Available.**

STUDENT KITS, ENGG. KITS & PROJECTS

**PIR Sensor, Ic & COB For Sound Effect,
Waterfall, Doorbell, Clock, Alarm,**

RF MODULES TX - RX - TR ASK - FSK - AV

**Led Flasher, MCU with Speech & Melody,
Custom Design Asic etc.**

S.M. SEMICONDUCTORS

Ground Floor Bakul Baug, Vasundhara, Opp. Indian Bank,
S.V. Road, Santacruz (West), Mumbai - 400 054

Tel. : 022-2618 2082 / 2617 3575 Fax : 91-22-26118035

Mobile : 9833374818 Website : www.aplusindia.net

E-mail : sales@aplusindia.net / sms003@sms003.com



ISO 9001:2008 CERTIFIED



Industrial Loads
Range : 1KW - 300KW



Low Ohmic Power Resistors
Open Frame Axial & PCB Mounting
Range : 0.001 - 1 ohms Power : 0.5 W - 3 W
Tolerance : ±5%, ±2%, ±1%



Resistors Adjustable / Fixed
(Silicone Coated)
Range : E 001 - 500 K Power : 0.5 W - 5000 W
Tolerance : ±5%, ±2%, ±1%



Resistors Ceramic Encased
Range : E 001 - 100 K
Power : 2 W - 50 W
Tolerance : ±5%



Resistors Aluminum Housed
Range : 0.1 ohms - 100 K ohms
Power : 5W - 1000 W
Tolerance : ±5%



Dynamic Breaking Resistor
Range : E1 - 100 K
Power : 40 W - 10000 W
Tolerance : ±5%



Rheostat (Open / Covered / LSA)
Range : 0.5 ohms - 10000 ohms
Power : 0.1 Amp - 200 Amp



Potentiometer (Single / Gang Type)
Range : 1 ohms - 10 K ohms
Power : 25 W - 1000 W
Tolerance : ±5%

STEAD ELECTRONICS (INDIA) PVT. LTD.

Sales Office : 1681/20, Mangal Market, Bhagirath Palace, Delhi-110006

Ph. : 23865929, 23862576 Fax : 011-23867465

Regd. Office : 17 U.A. Jawahar Nagar, Delhi-7

e-mail : sales@steadresistors.com visit at www.steadresistors.com

MAXEL™
AN ISO 9001:2008 CERTIFIED CO.

**Complete Range
LED Drivers**



Output : 12VDC/350 MA



Output : 21VDC/350MA



Output : 21VDC/350 MA



Output : 42VDC/350MA



Output : 12VDC/10 AMP

Features

- Constant Current
- Universal Input Range (95VDC-290VDC)
- Short Circuit Protection
- Available upto 150 Watts
- Available in open & Close Form



Solar Charge Controller

- Voltage: 12VDC to 96VDC
- AMP: 5AMP to 30 AMP

MAXEL ELECTRONICS SYSTEMS PVT. LTD.

2097/22, Balaji Market, Chahindra, Bhagirath Palace, Delhi-06

Ph. : 011-23867603, 47506700, Call : +91-9811205116

E-mail : maxelsystems@rediffmail.com

Website : www.maxelelectronics.com

Plastic Cabinets



Desk-Top Enclosure



Water-Proof Enclosure



Pushwheel Switches
14mm & 22mm

UNIVERSAL ELECTRONIC AGENCIES

1582-1583, 11nd Floor, M.J. Building, Bhagirath Palace,
Chandni Chowk, DELHI - 110 006.

Ph. : +91-11- 23862646/23865910, Fax : 23860661

E-mail : harinder@vsnl.com, Web. www.easternradio.co.in