



HELIO
Heli Optoelectronics Corporation
Taiwan
Power LEDs
1 watt/3 watt /COB -13/17 watt
Heli-Rebel / H-Lamp

AUTHORISED DISTRIBUTORS

ZMDI
The Analog Mixed Signal Company
Zentrum Mikroelektronik Dresden
AG (GERMANY)
I C for LED drivers with only 4 external components * Dimming Feature
* LED protection with NTC.
Models: ZLED 70xx series

AUTHORISED DISTRIBUTORS

3M
WORLD LEADER IN THERMAL MANAGEMENT
The tapes and pads have

- Excellent Thermal Conductivity
- Very Good Electrical Insulation
- No need for Heat Sink Paste or Compound
- Hyper-soft material

VELTRON ELECTRONIC DEVICES PVT. LTD.
52/c Chotani Bldg., 2nd Floor, Proctor Road, Grant Road (East), Mumbai 400 007 India
Mob: +91 99 207 988 48, Tel: +91 22 2861 1032 / 3242 0719
E mail: sales@veltronindia.com, Web Site: www.veltronindia.com,

AUTHORISED DEALER FOR

PHENIX CONTACT
COMBICON / CLIPLINE / PLUSCON / INTERFACE / TRABTECH.

PROTECTION
CONNECTORS/RESETTABLE & BLADE FUSES

INCAP LIMITED
ELECTROLYTIC CAPACITORS

GUARDIAN CONTROLS LIMITED
INDUSTRIAL, AUTOMOTIVE & TELECOM RELAYS

ESSEN
ELECTRONIC CONNECTORS, SWITCHES, RELAY SOCKETS & ELECTRICAL PRODUCTS

CARBON FILM, METAL FILM & CHIP RESISTORS.

watts RESISTORS

BC COMPONENTS
7/B, Ahmed Mansion, Chunam Lane, Lamington Road, Mumbai-400 007.
Phone : 2387 2308 Telefax : 2388 2332 E-mail: bc@bccomp.net

Solar energy committed to a lifetime of safety and performance

CTSR

LEM commits to renewable energy sources of the future by enabling control and ensuring safety of today's solar power solutions. CTSR transducers combine safety and performance, accurately measuring small AC and DC leakage currents. Easy installation for single or three phase residual current measurement: CTSR is today's choice for the energy of tomorrow.

- Two nominal current ranges: 0.3 and 0.6 A_{RMS}
- Low offset drift
- Printed circuit mounting
- -40 to +105°C operation
- Large 20.1 mm diameter aperture
- Reference Voltage access and control
- Available with primary inserted conductor
- Self-test and degauss
- +5 V single supply
- High overload capability: 3300 A
- Up to 11 mm creepage and clearance distances
- + CTI 600 for high insulation



For enquiry/More information on LEM products, please contact:



No.122, 27th Cross, 7th Block, Jayanagar, Bangalore-560070
Ph: 080-26635776/26643375/26534013 Fax: 080-26534020
Email: sales@globetek.in Web: www.globetek.in

