

the router offers up to 450Mbps transfer rate over dual networks.

Web-surfing can be performed over



a standard 2.4GHz band, while performance-critical video transmission, such as Internet movies or online gaming can be performed over a 5GHz band simultaneously, without any interference between each other.

NBG5715 features four gigabit ethernet ports and two built-in NetUSB ports, which allow home users to share stored content in USB devices over the home network, without plugging the USB devices into different equipment.

ZyXEL, New Delhi

Fax: (011) 40523393

Phone: 47608800

Web: www.zyxel.in

## M2M smart services developer kit

Kontron has introduced machine-to-machine (M2M) smart services developer kit with a deployable Intel Atom-based services-ready system.

The computer-on-module (COM)-based kit includes M2M system carrier board and AV board to support headed configuration use. It is 802.11a/b/g/n wireless local area network (WLAN)- and 802.15.4 wireless personal area network (WPAN)-capable. 3G wireless wide area network (WWAN) is either pre-installed or enabled by dropping in a pre-certified PCI Express 3G/4G module for further broadband connectivity flexibility.

The M2M solution and kit packaging may be customised to include the network operator's, original equipment manufacturer's or independent software vendor's brand.

Kontron Technology India Pvt Ltd, Bengaluru  
Fax: (080) 40831001

Phone: 40831000

E-mail: salesindia@kontron.in

Web: www.kontron.com

## Multi-Port VoIP-GSM-ISDN BRI gateway

Matrix Comsec has added SETU VGB to its VoIP gateway portfolio. The GSM/3G-ISDN BRI gateway interfaces with an existing ISDN PBX to offer GSM/3G and IP connectivity. For an IP-based system it provides BRI and GSM/3G trunking options.



SETU VGB can be used to set up IP connectivity between multi-location offices and get advantage of

low-cost VoIP calling among the distant branches. Apart from providing IP calling to traditional PBX users, it also offers data accessibility over UMTS/HSPA/EDGE networks. SETU VGB offers up to nine SIP accounts that can be registered either to single or multiple service providers to make VoIP calls.

Matrix Comsec, Vadodara

Fax: (0265) 2636598

Phone: 265 2630555

Web: www.MatrixComSec.com

## MISCELLANEOUS

### Evaluation boards

Bourns has introduced two new evaluation boards for RS-485-based applications. The boards have been developed as a design resource that streamlines evaluating circuit protection on RS-485 serial device ports.

To meet the required industry standards on RS-485 port interfaces, the boards provide two different evaluation approaches. The RS-485EVAL-



BOARD1 includes two Bourns TBU high-speed protectors (HSPs), two Bourns fast-acting GDTs and two Bourns TVS diodes. The RS-

485EVALBOARD2 uses Bourns TBU HSPs, MOVs and TVS products.

Bourns Asia Pacific, Inc.

Web: www.bourns.com

### 3D printer

Amp Tronics has launched a mini rapid prototype 3D printer. The desktop sized printer uses acrylonitrile butadiene styrene plastic 1.72mm filament as print material and can produce fairly large models.

The printer uses standard 'stl' files and comes with software to convert these files and send them to the printer.



The 5kg printer has power requirement of 100-240AC, 50-60Hz, 220 watts and a maximum build size of 140x140x135mm<sup>3</sup>.

Most of the inside parts of this printer are enclosed with the exception of the automatic feed motor. The frame is made from powder-coated metal and screwed together.

Amp Tronics, Hyderabad

Phone: (040) 23320240

E-mail: info@amp-tronics.com

### Vector signal analyser

National Instruments has introduced a 14GHz version of its NI PXIe-5665 vector signal analyser (VSA). The VSA consists of NI PXIe-5605 down-converter, NI PXIe-5653 local oscillator synthesiser and a 150MS/s intermediate frequency

(IF) digitiser NI PXIe-5622. It features third-order intercept point at +24dBm

with an absolute amplitude accuracy of  $\pm 0.10$  dB and error vector magnitude of 0.33 per cent for a 256 QAM modulated signal. It also delivers low-phase noise of -129 dBc/Hz at a 10kHz offset at 800 MHz and an average noise level of -165 dBm/Hz.

NI Systems (India) Pvt Ltd, Bengaluru

Phone: (080) 41190000

E-mail: ni.india@ni.com