

Power Packed Resistors From

WIRE WOUND RESISTORS



CURRENT SENSE RESISTORS

HIA

Power Axial Type.
Power Rating : 0.5W to 20W
Resistance Range : R01 to 120K
Tolerances Available : 10%, 5%, 3%, 1%
Features : • Flame retardant. • Pulse type available. • Thermocoat precision power. • Non-inductive type available.

HFP

Power type PCB mounting.
Power Rating : 2W to 8W (at 70°C)
Resistance Range : R10 to 59K
Tolerances Available : 10%, 5%
Features : • Low cost. • Automated assembly and wave soldering possible. • Commercial applications.

HSR

Capacitor discharge.
Wire wound symmetry resistors
Power Rating : 8.25W & 11W (70°C)
Resistance Range : 10K to 70K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Stainless steel mounting terminals for direct mounting on to capacitors.

HCA/HCV

Power Axial type
Power Rating : 1W to 20W (70°C)
Resistance Range : R10 to 56K
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • High insulation. • Fire proof. • Resistant to aggressive solvents. • Pulse type available. • Bracket acts as heat sink.

OA / OP

Open Frame / Axial and PCB Mounting - Shunt Type.
Power Rating : 0.5W to 5W (85°C)
Resistance Range : R002 to R10
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Non insulated. • Surge / current sensing applications.

BR

Slit type Metal Plate / Preformed Resistance Strip.
Power Rating : 2W to 10W (70°C)
Resistance Range : R01 to 1R2
Tolerances Available : 10%, 5%
Features : • Radial configuration. • Negligible inductance. • Choice of 3 different preformings available.

RL

Alloy ribbon element in cylindrical ceramic body.
Axial type.
Power Rating : 0.5W to 10W (25°C)
Resistance Range : R002 to R80
Tolerances Available : 10%, 5%, 3%, 2%, 1%
Features : • Negligible inductance. • Replaces moulded type.

FUSIBLE RESISTORS

(Safety Version)

FRS

Wire wound type.
Power Rating : 1W to 5W
Resistance Range : 10R to 3K3
Tolerances Available : 10%, 5%
Features : • Fire retardant coating. • UL requirements met satisfactorily. • Fail safe 'safety version' available.

HI-TECH RESISTORS PVT. LTD.

AN ISO TS 16949: 2009 CERTIFIED COMPANY
Buty Compound, Mount Road Extension, Nagpur-440 001, INDIA.
Tel: +91-712-2531134, 2533269, 2553691. Fax: +91-712-2528334, 2556351.
e-mail : info@htr-india.com | www.htr-india.com



Metaphors

SMD ELECTRO COMPONENTS

FULL RANGE OF SMD ACTIVE & PASSIVE COMPONENTS

Authorised Distributor



SMD I-Capacitors



SMD Transistors
SMD SMD SMD Inductors
SMD Capacitors



SMD Resistors

CHIP TRANSISTORS / CHIP DIODES / CHIP LED's / CHIP CAPACITORS / CHIP IC's

- CHIP RESISTORS
- CHIP BRIDGE RECTIFIERS
- CHIP FERRITE BEADS
- CHIP RESISTOR NETWORKS
- CHIP TRANSDUCER VOLTAGE
- CHIP HALL SENSORS
- CHIP CAPACITORS
- SUPPRESSORS
- CHIP IR LESS & SENSORS
- CHIP TANTALUM CAPACITORS
- CHIP IC'S
- CHIP POTENTIOMETERS
- CHIP ELECTROLYTIC CAPACITORS
- CHIP MOSFETS
- CHIP FUSES
- CHIP ZENERS & DIODES
- CHIP REGULATORS
- CHIP SWITCH
- CHIP TRANSISTORS
- CHIP DIPT COUPLERS
- CHIP MOV'S
- CHIP LED'S
- CHIP PRIMER CAPACITORS
- CHIP THERMISTORS
- CHIP SCHOTTKY DIODES
- CHIP INDUCTORS
- CHIP SOLDER PASTE
- CHIP SOLDER WIRE 28 SMD



54-C, Jyoti Estate, Proctor Road, Near Parijat bldg., Off. Lamington Road, Mumbai - 400 007, INDIA. Tel: 91-22-3240 2444 • Mob: 93242 11912

E-mail : smdelectro@vsnl.net

FOR ALL YOUR ELECTRONIC COMPONENTS NEED

www.icsemiconductor.com

Visit us:

electronica India 2011 & productronica India 2011

Exhibition

HALL NO. 12 A, BOOTH NO. 2021 / 2023
PRAGATI MAIDAN, NEW DELHI

DATES: 13th TO 16th SEPT 2011