

Conduction Cooling has arrived.

Diamond Systems introduces

EPSILON


8-Port Gigabit Ethernet Switch



- ◆ Advanced 8-port Gigabit Ethernet switch
- ◆ Layer 2 managed switch
- ◆ Wide input DC/DC power supply
- ◆ Rugged design
- ◆ Extended temperature operation of -40°C to +85°C
- ◆ Heat spreader for conduction cooling
- ◆ Innovative power management
- ◆ PC/104 form factor (3.55 x 3.775 in.)

Discover the benefits of conduction cooling:

- ◆ Enhances reliability by keeping the processor cooler than traditional heat sinks.
- ◆ Frees the top side of the board to make adding I/O expansion modules easier



FeaturePak™ is a trademark of the FeaturePak Trade Association. PC/104™ and PC/106-Plus™ are trademarks of the PC/104 Embedded Consortium. SUMIT™ is a trademark of the SFF-SIG. All other trademarks are the property of their respective owners.

Authorized Distributors in India



**EMBEDDED SYSTEMS
SOLUTIONS**

www.embeddedindia.com

sales@embeddedindia.com

BANGALORE: 9845149926

CHENNAI: 9841053251 DELHI: 9810260353

HYDERABAD: 9848655337 PUNE: 9923546346

Other products in Diamond's family of conduction-cooled systems...

Aurora PC/104 SBC

- ◆ 1.6GHz Intel® Atom™ Z530 CPU
- ◆ Up to 2GB rugged SO-DIMM memory
- ◆ PC/104 size, 3.55" x 3.775" / 90 x 96mm
- ◆ PC/104 and SUMIT™ I/O expansion
- ◆ -40° to +85°C operation
- ◆ Meets MIL-STD 202G shock and vibration levels



Pluto ETX SBC

- ◆ ETX format, 3.74" x 4.49" / 95 x 114mm
- ◆ Choice of Intel® N270, N450, or Core Duo processors
- ◆ 2 LAN, 4 COM, 2 SATA, CompactFlash
- ◆ PC/104-Plus expansion
- ◆ -40° to +85°C operation



Magellan COM Express SBC

- ◆ COM Express™ format, 3.74" x 4.92" / 95 x 125mm
- ◆ Choice of Intel® Z510 1.1GHz or Core 2 Duo™ LV 1.6GHz processors
- ◆ 2 Gigabit LAN, 4 COM, 1 SATA, 1 flashdisk
- ◆ PC/104, SUMIT, and FeaturePak™ expansion
- ◆ 7-36VDC wide range input
- ◆ -40° to +85°C operation



Neptune EPIC SBC

- ◆ EPIC format, 6.5" x 4.53" / 165 x 115mm
- ◆ Choice of Intel® N270, N450, or Core Duo™ Processors
- ◆ On-board 16-bit A/D, D/A, digital I/O and optoisolated I/O
- ◆ PC/104-Plus™ expansion
- ◆ 7-28VDC wide range input
- ◆ -40° to +85°C operation



**DIAMOND
SYSTEMS**

www.diamondsystems.com