

New !!

Part Number	LL01CR-OFxL-Mx	LL01CR-SQxL-Mx	LL01OS-MQxL-Mx	LL01CR-PPxL	LL03CR-RxL	LL03NI-QQxL
Picture						
DxH(mm)	17.1x10.5	21x13.9	21x14.3	45x23.6	35x8	35x10.5
Degree	25° 40° 60° 90°	40° 60°	25° 40° 60°	45° 60° 80°	40° 60°	15°
LED	Cree XPG	Cree XPG/EP/PG/ML/RE/AM Edison 1LA5 Nichia 0030	Osram Oscon 80°	Cree ML/C/CL233 Edison Engower(S Chip)	Cree XPC/XPE/XPG	Nichia 119

Hot !!

Part Number	LL01CR-DOxL-Mx	LL03CR-AxL	LL03ED-OKxL	LL03ED-APxL	LL04U-DOxL	LL05CR-FRxL
Picture						
DxH(mm)	32.9x18	50.5x13	33.2x12.1	50.5x18.6	67x12.56	35.8x5.5
Degree	22° 36° 40° 50° 60°	25° 45° 60°	25° 40° 60°	10° 30° 45° 60° 40°x70°	15° 25° 40°	25° 40° 60°
LED	Cree MCE	Cree XPE	Cree XPC/XPE/XPG Edison Federal Lumileds Rebel/Nichia 119 Seoul ZS/Osram Oscon	Edison 1LA5 Nichia 0538/183 Seoul P4/21	Cree XPC/XPE/XPG Edison Federal Lumileds Rebel/Nichia 119 Seoul ZS/Osram Oscon	Cree XPE/XPG Edison Federal

Street Lighting !!

Part Number	LL01CR-KM6090L	LL01LU-UQ70140L	LL01OS-AU60140L	LL01ED-LP70130L	LL01CR-XW70140L	LL24CR-AU70130L
Picture						
DxH(mm)	20x11.6x8.6	18x11x8.1	16x8.7x4.8	20.1x11.8x9.4	32x17.6x8.8	120x100x10.2
Degree	60°x90°	70°x140°	60°x140°	70°x130°	70°x140°	75°x135°
LED	Cree XPE	Lumileds Rebel	Osram Oscon 80°	Edison 1L58	Cree XML	Cree XPC/XPE/XPG Lumileds Rebel

With integration of optical design, mould tooling, and mass production in house, Ledlink offers professional optical solution and various types of semi-module products. Our mission is to provide just in time services along with cost effective and optimised performance secondary lens for innovating LED lamps. Please contact us for further information or visit our website for our latest products.

precious Electronics Pvt. Ltd. (Authorized Distributor & stockist)
52-C, Chottani Building, Procter Road, Grant Road (E),
Mumbai 400007 Phone: 91-22-23869473 / 23869472
email: deepak@precious@yahoo.co.in
ledlink@preciouselectronics.com
www.precouselectronics.com

ChipSESD Protection Devices

ChipSESD protection devices help protect electronic circuits against damage from electrostatic discharge (ESD) events. The 0201-sized ChipSESD device's miniature footprint - measuring 0.6 x 0.3 x 0.3mm - is approximately 70% smaller than prior-generation devices, offering designers placement flexibility in space-constrained applications.

APPLICATIONS & FEATURES

- Mobile phones, portable and consumer electronics
- Applications requiring high ESD performance in a small package
- SMD passive package is easier to install and rework vs. traditional semiconductor packages
- Bi-directional operation eliminates the need for PCB installation polarity inspection
- Helps equipment pass IEC61000-4-2, level 4 testing

For more information, please visit www.circuitprotection.com/sesd

© 2011 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All rights reserved. • www.te.com
TE Connectivity, TE Connectivity (Logo) and TE (logo) are trademarks.
Tel: 91-80-41613745 Email: badsha@te.com