

speed video switch enhancing resolution and refresh rates for commercial



displays, gaming monitors, docking stations, video-matrix switches, and embedded

applications. The wide signal-voltage range supports DC-coupled operations, enhancing signal integrity. Priced at \$1.65 for 3500 pieces, it is ideal for high-performance video applications.

Diodes Incorporated

<https://www.diodes.com>

Gate driver for industrial use

Littelfuse, Inc. have announced the IX4352NE Low-side SiC MOSFET and IGBT gate driver, designed for industrial applications using silicon



carbide (SiC) MOSFETs and insulated gate bipolar transis-

tors (IGBTs). It eliminates the need for external power supplies, saving space. Ideal for chargers, PFC systems, converters, and motor controllers, it integrates protection features like desaturation detection, UVLO, and thermal shutdown, enhancing safety and reliability.

Littelfuse

<https://www.littelfuse.com>

High-power dual-chip UVC LEDs

Marktech Optoelectronics has introduced dual-chip UVC LEDs, available in 235nm and 255nm wavelengths,



doubling the output of traditional single-chip LEDs. These high-power LEDs

meet the growing demand for deep UVC light sources in purification and instrumentation. By integrating two UVC LEDs in one package, Marktech enhances light output, crucial for water purification, air and surface sanitisation, and sterilisation.

Marktech Optoelectronics

<https://marktechopto.com>

Isolated DC/DC converters

RECOM has launched a new series of isolated through-hole DC/DC converters ideal for space-limited configurations, available in 10W, 20W, and 30W



models. They cater to electronics designers, automotive professionals,

industrial automation firms, telecom companies, and aerospace and defence sectors. With comprehensive protection features, low ripple and noise, and a $\pm 10\%$ output voltage adjustment, these units are efficient and meet IEC/EN/UL62368-1 isolation standards.


RECOM

<https://recom-power.com>

EMBEDDED

Compact SBC for edge computing

IBASE Technology Inc. launched the IB200, its first ultra-compact 6.35cm (2.5-inch) single board computer



(SBC) for edge computing. Featuring AMD Ryzen Embedded R2000 Series with 4 cores

and 8 threads, and integrated AMD Radeon Vega graphics, it doubles the CPU core count over the R1000 Series. Key features include 8GB DDR4 memory, dual HDMI 2.0b ports for 4K displays, dual GbE LAN, four COM ports, USB 3.2 Gen2, and M.2 slots. With a 12-25W thermal design, it suits industrial IoT applications.

IBASE

<https://www.ibase.com.tw>

SiC moulded modules for EVs

ROHM introduces four new models in the TRCDRIIVE pack series, featuring 2-in-1 SiC moulded modules for electric vehicle traction inverters. The series includes two 750V models and two 1200V models, supporting up to 300kW. These modules address miniaturisation,

efficiency, and installation challenges, boasting industry-leading power density,

Evaluation Kit for Double-Pulse Testing

Evaluation Kit for 3-Phase Full Bridge Applications



low inductance, and simplified installation.


Featuring 4th Gen SiC MOSFETs, they enhance heat dissipation and reduce losses. Mass production capacity is 30 times higher than conventional modules, with samples available and expanded models expected by March 2025.

ROHM

<https://www.rohm.com>

Xilinx system-on-module

MYIR's MYC-J7A100T system-on-module, powered by the Xilinx Artix-7 XC7A100T FPGA. With 260-pin MXM Gold-finger-edge-card expansion, it offers 178 FPGA I/Os, four GTP high-speed transceiver interfaces, and a



JTAG interface.

Operating at $-40 \sim 85^{\circ}\text{C}$, it is ideal for industrial control

and automation. The MYD-J7A100T development board supports enhanced evaluation with extensive communication interfaces and optional add-ons.

MYIR

<https://myir.ird.govt.nz>

Safety unit for industrial robot

Yamaha Motor Co., Ltd has launched the RCX3-SMU, a functional safety unit for SCARA and Cartesian robots



controlled by the RCX340 controller. This unit addresses rising

safety demands in industrial automation due to labour shortages and cost increases. Key features include safe torque off (STO), safe stop 1 (SS1), and speed monitoring (SLS). Additional functions include area monitoring and safety input/output monitoring for enhanced operational safety.

Yamaha Motor Co., Ltd

<https://global.yamaha-motor.com>