

TEST & MEASUREMENT

Portable digital multimeters

MECO's digital multi-range portable meters, classified as Class 0.5 instruments, offer precise measurements for continuous AC TRMS and DC operations. Featuring a backlit display,



versatile orientation options, and a robust housing with a tilt handle, these meters ensure accuracy through advanced microcontrollers and surface mount technology.

With four models covering A AC, A DC, V AC, and V DC measurements, each offering five ranges, these meters replace the need for multiple instruments and offer USB connectivity and user-friendly interface software for easy data management. They are ideal for laboratories, schools, workshops, and field measurements, serving as master standard meters for verification and re-calibration.

MECO

<https://www.mecoinst.com>

6½-digit multimeter

Uni-Trend Technology has unveiled the UT8806E bench top 6½-digit digital multimeter. What sets it apart is the True RMS AC voltage and current measurement feature, ensuring precise readings even in fluctuating and non-sinusoidal waveforms.



With a frequency response up to 300kHz, it suits diverse applications. The UT8806E boasts remarkable DC voltage accuracy at 0.0035% and a minimum resolution of 0.1μV for AC voltage and 1pA for DC current. It operates at a speed of up to 10000 readings per second. A 10.9cm TFT LCD supports dual display function-

ality. Connectivity options include USB host and device, LAN, RS232-C ports, and an optional GPIB interface, backed by 10k readings and 32GB of Nand Flash memory. The UT8806E is ideal for professionals in embedded systems, IoT, power supply, industrial control and automation, ATE bench integration, academia, and research sectors requiring precision, speed, and connectivity.

Uni-Trend Technology

<https://www.uni-trend.com>

MISCELLANEOUS

Compact dual-output LCD bias power supplies

Nexperia has unveiled dual-output LCD bias power supplies to enhance TFT-LCD panel longevity in smartphones, tablets, VR headsets, and



LCD modules. The NEX10000 and NEX10001 models

boast I²C programmable asymmetric voltage outputs and a cost-saving single-inductor compensation design, reducing PCB space. Peak efficiency reaches 86% at 40mA and 5% at 80mA, with a compact form factor of 1.16mm × 1.96mm × 0.62mm. These power supplies aim to enhance efficiency and device lifespan in handheld electronics and displays. Irene Deng, General Manager at Nexperia, highlighted their commitment to compact, high-performance devices, emphasizing the NEX10000/1's precision output and efficiency for extended battery life and display longevity.

Nexperia

<https://www.nexperia.com>

Developer platform for AI SoCs

Ambarella, Inc. introduced the Cooper developer platform, offering comprehensive support for their AI systems-on-chip (SoCs). Core includes a Linux-

based OS and development kits, while Foundation features a Model Garden of pre-trained neural network models. Vision aids multi-modal sensor processing and fusion, while UX offers a



user interface and debugging tools. Fermi Wang, Ambarella's President

and CEO highlighted the platform's ability to simplify AI development, abstracting hardware complexity. Integration with open source tools like TensorFlow and ROS2 enhances accessibility. The platform also expands through AI-acceleration PCIe cards, SoM manufacturers, and collaborations with design and manufacturing service providers.

Ambarella Inc.

<https://www.ambarella.com>

Compact low-power LCOS panel

OmniVision, a global semiconductor solutions developer, introduces the OP03050—a compact, low-power liquid crystal on silicon (LCOS)



panel that integrates LCOS array, driving circuit, frame

buffer, and interface, enabling high-resolution visuals ideal for real-time video conferencing and streaming in AR, XR, and MR glasses and head-mounted displays. LCOS technology, featuring a 3.0-micron pixel pitch, and 4-channel MIPI-DSI interface support, finds applications in medical, engineering, and aerospace sectors. This single-chip LCOS panel, combining display, drivers, and frame buffers, offers clear, stable images without retention, enhancing visual experiences. Its power-efficient design reduces consumption by 40%, delivering exceptional image quality and stability.

OmniVision

<https://www.ovt.com>