

significantly reducing inverter size and installation time.

ROHM

<https://www.rohm.com>

Pre-driver for massive MIMO systems

Qorvo has introduced the QPA9822, the highest gain pre-driver in the industry, offering 39dB gain at 3.5GHz and peak



power of +29dBm.

This component advances 5G technology and reinforces the company's leadership


in cellular infrastructure. Housed in a compact 16-pin, 3x3mm SMT package, it is footprint and pin-compatible with the QPA9122M amplifier. Designed for 32-node massive MIMO (mMIMO) systems, the QPA9822 supports 5G NR bandwidths up to 530MHz, ideal for the N77 band. With 50 ohms internal matching, a fast enable/disable function, and external bias control, it ensures easy integration and rapid deployment for 5G systems.

Qorvo

<https://www.qorvo.com>

16W AC/DC converters for diverse applications

RECOM has introduced new 16W AC/DC converters in its RACM16E-K/277 series, measuring 5.08 x 2.7 x 2.2 cm (2 x 1.08 x 0.9 inches), available in



standard pinned and wired configurations. These converters serve

sectors like electric vehicle chargers, industrial automation, lighting, IoT, medical devices, and measurement

equipment, emphasising stability, efficiency, and strict safety standards. Certified for medical use, they operate efficiently under light loads within -40°C to +85°C. They support 85V to 305V AC input, offering 3.3V to 30V outputs, with the 3.3V model providing 12W. Features include short circuit protection and compliance with IEC 62368, IEC 61558, EN 60335, and UL/IEC/EN 60601 standards.

RECOM

<https://recom-power.com>

3D HAL sensor for automotive and industrial use

TDK Corporation has expanded its Micronas 3D HAL position sensor line with the HAL/HAR 3936, enhancing Hall-



effect-based 3D position sensors for automotive

and industrial applications. The HAL/HAR 3936 offers advanced magnetic position processing, ideal for steering column switches, gear selectors, and brake sensors. Compliant with ISO 26262 standards, it features a low-power mode for direct battery connections, enhancing energy efficiency. With a built-in SENT interface and configurable PWM or SENT outputs, it adapts to various applications. The sensor meets ASIL C standards, operates from -40°C to 150°C, and is available in SOIC8 and SSOP16 SMD packages.

TDK Corporation

<https://www.tdk.com>

Distance detection sensors

Hikrobot has introduced machine vision photoelectric sensors in India,

designed for diverse distance detection needs across industries. These sensors use visible and infrared light to meas-



ure changes in reflected or blocked light, providing non-contact

detection to prevent damage and eliminate maintenance. They maintain stability in environments with high-frequency electromagnetic interference and noise. IP67 certified, the sensors resist sunlight, LED light sources, and electromagnetic environments. They feature pinpoint and laser technologies for long-distance detection and are suitable for applications like long-range detection, distance measurement, and monitoring reflective or transparent objects. Hikrobot focuses on IIoT, logistics, and manufacturing.

Hikrobot

<https://www.hikrobotics.com/en>

Military and aerospace power supplies

Gaia Converter has expanded its military and aerospace power systems



with the PSDG-48 series board mount module, featuring isolated power supplies with 2 or 3 outputs, each providing 48W.

Designed for 24V and 28V DC military applications, it meets MIL-STD-461, MIL-STD-704, MIL-STD-1275, ABD100, and DO160 standards. Key features include an integrated EMI filter, reverse polarity protection, and a 50ms hold-up function. It handles high/low input voltage transients, inrush cur-



**WE LOVE TO
SHOWCASE
NEW PRODUCTS!**

Launched a New Product related to electronics?

Share its details with us at newproduct@efy.in
Send a photo too. We will be happy to review it, and if it matches our guidelines— we will publish it here, for FREE!