

standard PCBs with tested ones for effective fault diagnosis. The system supports all component technologies with a maximum fly height of 100mm and dual live video cameras, ensuring precise, cost-effective troubleshooting and quick fault localisation, minimising time to market.

Polar Instruments GmbH
<https://www.polarinstruments.com>

MISCELLANEOUS

Software update to speed up circuit testing

XJTAG has released version 4.0 of its software suite, featuring significant speed enhancements and improved user interface for better efficiency. The key update is the multi-TAP performance enhancement through opti-



mised scans, enabling the XJLink2 controller to operate multiple JTAG chains concurrently at varied clock speeds. This prevents slower chains from reducing the data transfer rate of faster ones, improving test times. Engineers and production line operators benefit from these updates, which facilitate more efficient testing across entire circuits and better visualisation of outputs. The redesigned boards screen and intuitive test reset sequence editor further streamline the testing process.

XJTAG
<https://www.xjtag.com>

Efficient and accurate indoor positioning solution

u-blox has launched u-locate, an indoor positioning solution utilising Bluetooth LE AoA technology, offering 10cm accuracy with extended tag battery life and cost efficiency. Ideal for RTLS providers and systems integrators, u-locate supports applications in warehousing, manufacturing, and healthcare. It features advanced AoA

algorithms, Bluetooth 5.1, and an optimised antenna for high precision and power efficiency. The modular



solution includes u-locateHub, u-locateEngine, u-locateAnchor, and u-locateTag,

and integrates with GNSS for seamless indoor-outdoor localisation. Compliant with the omlox standard, it offers OTA updates and extensive management tools, enhancing operational efficiency and sustainability in various industries.

u-blox
<https://www.u-blox.com/en>

Motor control unit for 2- and 3-wheel EVs

FRIWO is expanding its electromobility portfolio with the MC1.5-55A-48V motor control unit, targeting the Asian markets of India, Vietnam, Indonesia, and Southeast Asia. This unit, designed for 2- and 3-wheel



electric vehicles, offers a continuous power output of 1.5kW, an operating voltage range of 30-72V, and a motor current capacity of 100A RMS. It ensures robust performance under challenging conditions with an IP65 protection rating for durability in high ambient temperatures. Supporting permanent magnet synchronous motors (PMSM), it integrates sensors via two analogue and nine digital inputs, with CAN protocol for communication. The Enable Tool software complements it for precise motor control, firmware updates, and secure data management.

FRIWO
www.friwo.com

Full HD video streaming PoE camera

e-con Systems has introduced RouteCAM_CU25, a new global shutter

GigE camera in the RouteCAM series. This full HD PoE camera is ideal for traffic systems, road safety, law en-



forcement, and forklift safety. Key features include PTP

synchronisation for precise multi-camera timing, integration with the cloud-based CloVis central platform for remote device management, and compliance with industrial standards (ISO 16750, ISO 20653:2013). The IP67-rated camera supports full HD video streaming in MJPEG, H.264, and H.265 formats. It offers HD and full HD at 60 fps, uses a shielded Cat6 cable, and supports multiple ethernet modes.

e-con Systems
<https://www.e-consystems.com>

Data loggers for temperature and humidity monitoring

BrainChild Electronics has launched the XH series of temperature and humidity data loggers for various industries. These devices integrate into smart manufacturing systems, optimising production conditions



and enhancing decision-making. In logistics and warehousing, they maintain goods' integrity, particularly in cold chain logistics. Biotechnology and pharmaceutical sectors benefit from their use in vaccine storage and transportation, ensuring product safety. Key features include compact design, $\pm 0.3^{\circ}\text{C}$ temperature accuracy, 13-month battery life, 80,000 data entry capacity, LCD display, one-key start/stop, USB interface, configurable sampling rates, and IP65 protection. These loggers are essential for precise, real-time monitoring and analysis.

BrainChild Electronics
<https://www.brainchildtw.com>