

12-Bit Family



SDS800X HD SDS1000X HD

- SDS800X HD / SDS1000X HD
- 12-bit high resolution
- Sampling rate up to 2 GSa/s
- Memory depth up to 100 Mpts
- 7 inch / 10.1 inch touch screen
- 70 MHz, 100 MHz, 200 MHz / 100 MHz, 200 MHz

- 100 MHz, 200 MHz, 350 MHz models
- 12-bit High Resolution
- Sampling rate up to 2 GSa/s
- Record Length up to 200 Mpts
- Waveform capture rate up to 500,000 wfm/s (Sequence mode)
- Large 10.1" TFT-LCD display with 1024 * 600 resolution



SDS2000X HD



SDS3000X HD

- 350 MHz, 500 MHz, 1GHz models
- 12-bit high resolution
- Sampling rate up to 4 GSa/s
- Memory depth up to 400 Mpts
- Waveform capture rate up to 890,000 wfm/s (Sequence mode)
- Noise floor as low as 125 μ Vrms at 1 GHz full bandwidth

- Bandwidth up to 4 GHz, 12-bit ADC resolution
- Real-time sampling rate up to 20 GSa/s
- Record Length up to 1 Gpts
- Waveform capture rate up to 1,000,000 wfm/s
- Eye diagram, Jitter analysis, Compliance Test, Power analysis, Bode plot, decode, MSO, AWG
- SAP5000D, 5 GHz High-speed differential probe



SDS7000A

SIGLENT TECHNOLOGIES CO.,LTD

INDIA – Marketing, Sales & Service Support E-mail : rakesh.sen@siglent.com; sales@siglent.com
Cell No. : +91 83196 88725 Website : int.siglent.com