

ARE YOU LOOKING FOR URGENT PCB ?

DOUBLE & SINGLE SIDE

Metal Clad, CEM1, Paper Phenolic

DOUBLE SIDE
PCB SAMPLES IN

48 Hr

SINGLE SIDE
PCB SAMPLES IN

24 Hr

GET
10%
Discount
First
Order

✉ circuitelectronics2016@gmail.com

🌐 www.circuitelectronics.co.in



Fig. 11: Author testing the smartwatch touch keyboard

shown in Fig. 9. Solder the pins behind the Indusboard. The Indusboard size fits perfectly behind the display like a watch. Refer to Fig. 10 for soldering and placement of the Indusboard.

Testing

After proper assembly, power the Indusboard. When the code for the keyboard is uploaded, it shows the keyboard layout, and touching the keys will type the corresponding alphabets and letters. When the code for the mouse is uploaded, moving a finger on the display will move the mouse pointer along with the touch movements. Refer to Fig. 11 for the author's testing of the smartwatch touch keyboard. **EFY**

to the laptop. Refer to Fig. 7 for the code snippet for the keyboard. Fig. 8 shows the code snippet to detect the touch point and send as HID input.

After including all the libraries, upload the code by selecting the

ESP32S2 as the chip and the right port.

Circuit diagram

Connect the display and touch pins according to the circuit diagram

Ashwini Kumar Sinha, an IoT and AI enthusiast, is a tech journalist at EFY