


Every Bench. Every Engineer. Every Day.



SPS series DC Power Supplies
180 W – 1080 W



SSA series Spectrum Analyzers
9 kHz - 26.5 GHz



SDS series Digital Storage Oscilloscope
3 GHz - 4 GHz



SDM series Digital multi-Meters
4½ – 6½



SSG series RF Generators
100 kHz - 40 GHz



SDL series DC Electronic Loads
150 V/30 A, 200/300 W



SDS3000X HD series Digital Storage Oscilloscope

12-bit
HARDWARE

- 350 MHz, 500 MHz, 1GHz models
- 12-bit high resolution
- Sampling rate up to 4 GSa/s
- Memory depth up to 400 Mpts



SHA series Handheld Spectrum & Vector Network Analyzers
9 kHz - 7.5 GHz



SHS series Handheld Oscilloscope
100 MHz - 200 MHz



SDG series Waveform Generators
5 MHz - 1 GHz

Model	SDS3104X HD	SDS3054X HD	SDS3034X HD
Analog channels	4 + EXT		
Bandwidth	1 GHz (800 MHz in non-interleaving mode)	500 MHz	350 MHz
Sample rate (Max.)	4 GSa/s (interleaving mode), 2 GSa/s (non-interleaving mode)		
Vertical Resolution	12-bit, Up to 16-bit in ERES mode		
Digital channel (Optional)	16-channel; maximum sample rate up to 1 GSa/s; record length up to 100 Mpts		
Waveform capture rate (Max.)	Normal mode: 200,000 wfms/s; Sequence mode: 890,000 wfms/s		
Trigger type	Edge, Slope, Pulse width, Window, Runt, Interval, Dropout, Pattern, Video, Qualified, Nth edge, Setup/hold, Delay, Serial		
Probe (standard)	One 500 MHz passive probe supplied for each channel		
Display	10.1 TFT-LCD with capacitive touch screen (1024*600)		

Performance that fits your needs & budget

SIGLENT TECHNOLOGIES CO.,LTD

INDIA – Marketing, Sales & Service Support E-mail : rakesh.sen@siglent.com; sales@siglent.com
Cell No. : +91 83196 88725 Website : int.siglent.com

