

built on TSMC's N6 technology. With models delivering 25, 50, 100, and 200 TOPS, they suit industries like health-care, logistics, and defence.

SiMa.ai
<https://sima.ai>

Medical DC/DC converters

RECOM has introduced the REM2A and REM4A series of DC/DC converters, offering 2W and 4W outputs with




high medical-grade isolation. Available in through-

hole and SMD formats, these converters provide reinforced 5kVAC/1-minute isolation and 2MOPP rating at 250V AC, with creepage and clearance over 8mm. Designed for B, BF, and CF patient applications, they ensure ultra-low 2µA leakage current.

RECOM
www.recom-power.com

OptiMOS 6 MOSFETs

Infineon Technologies AG has expanded its OptiMOS 6 MOSFET portfolio with new 135V and 150V families, complementing its existing



120V range. Key improvements include up to

50% lower on-state resistance ($R_{DS(on)}$) and a 20% reduction in the figure of merit (FOM g), enhancing efficiency and power density. With the industry's lowest Q_{rr} , high avalanche ruggedness, and better EMI behaviour, these MOSFETs minimise switching losses.

Infineon Technologies AG
www.infineon.com

CMOS image sensor

OMNIVISION has launched the OX12A10, a 12MP CMOS image sensor



featuring TheiaCel technology, aimed at enhancing automotive safety through superior image qual-

ity in all lighting conditions. Designed for high-performance front cameras in ADAS and AD, it offers the highest resolution in 2.1µm TheiaCel family, following the 8MP OX08D10 and 5MP OX05D10 models. The sensor integrates LOFIC with proprietary DCG HDR technology to eliminate LED flicker and ensure exceptional performance.

OMNIVISION
<https://www.ovt.com>

12-channel LED driver

Diodes Inc. has introduced the AL58221, a 12-channel constant-current LED driver with 24V open-drain outputs, sinking up to 60mA



per channel. It ensures precise current regulation and $\pm 0.1\%$ output tolerance. It uses

adaptive pulse density modulation (APDM) to enhance refresh rates and reduce flicker, achieving over 1000Hz at 16-bit grayscale. Key features include a two-wire serial interface for grayscale control, a 10MHz clock input to minimise EMI, and pulse retiming for long-distance connections. It suits digital signage, lighting, and backlighting applications.

Diodes Incorporated
<https://www.diodes.com>

2W power amplifier

CML Micro has expanded its SpuRF line with the CMX90A006, a 2W power amplifier for ISM (915MHz) and SRD (868MHz) bands.



It operates on 2.5V-5.25V, working with single-cell lithium batteries, and fits industrial and IoT systems. The company claims to provide 52% efficiency, boosts signals by 33dB, and has an output strength of +42dBm with 26dBm per tone.

CML Micro
<https://cmlmicro.com>

OLED displays for extreme applications

Display Visions' OLED displays are designed to operate reliably across extreme temperatures, from -40°C to +80°C, with a fast 10µs response at -40°C and no afterglow. They suit



cold storage, outdoor devices, drying kilns, saunas, and machine rooms. These self-illu-

minating displays require no backlight, offering slim profiles (2mm-2.5mm) with consistent contrast and viewing angles, maintaining a 1000:1 contrast ratio. Available in white or yellow with polarizers and protective glass options, they feature 2.54mm pin grids and ZIFF connectors for easy integration.

Display Visions
<https://www.displayvisions.us/index.html>

EMBEDDED

AI camera

Raspberry Pi has launched an AI



**WE LOVE TO
SHOWCASE
NEW PRODUCTS!**

Launched a New Product related to electronics?

Share its details with us at newproduct@efy.in. Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!