

camera, a compact, affordable module developed with Sony. It features the IMX500 intelligent vision sensor, offering edge AI processing for real-time applications. Pre-loaded with the MobileNet-SSD



model for object detection, the AI camera performs all computations on-site, reducing strain on the connected Raspberry Pi SBC. With a Raspberry Pi RP2040 chip onboard, the camera is ideal for developers, hobbyists, and businesses, enabling efficient AI solutions across sectors without extra hardware.

Raspberry Pi

<https://www.raspberrypi.org>

Endpoint AI development board

Nuvoton Technology has released the NuEzAIM55M1 board to make AI development easier. It uses the ARM



Cortex-M55 core and includes a microcontroller with an online tool for training

models. The board helps developers quickly create AI models by collecting data and training image recognition models in minutes, even with little coding or AI knowledge. It is great for AI-powered devices like smart home products, industrial machines, and wearables.

Nuvoton

<https://www.nuvoton.com>

Single board computer

Logic Fruit Technologies has launched the Kritin iXD 6U VPX single board computer (SBC) for aerospace and defence. The SBC provides 64GB



DDR4 RAM across two memory channels and supports data transfer with Ethernet and PCIe Gen4. Customisable and aligned with the 'Make in India' initiative, it allows customers to upgrade or replace older SBCs.

The SBC handles tasks like improving

radar systems, analysing intercepted signals, supporting EO/IR sensors, managing electronic warfare, and providing computing for missions.

Logic Fruit Technology

<https://www.logic-fruit.com>

COM express compact module

Congatec has introduced the conga-TCR8, a COM express compact module powered by AMD Ryzen Embedded 8000 Series processors, featuring up to eight Zen 4 cores, an AMD XDNA NPU, and Radeon RDNA 3 graphics. These modules deliver up to 39



TOPS for AI inference and

offer a TDP range of 15W-54W with support for up to 128GB RAM, making them suitable for AI, medical imaging, gaming, and POS/POI systems. With a compact design, six PCIe Gen 4 lanes, optional onboard NVMe SSD, support for four 8K displays, and pre-installed OS options, they simplify system integration and deployment.

Congatec

<https://www.congatec.com/us>

Mini-ITX motherboard

DFI has launched the RPS101/RPS103 Mini-ITX motherboard, supporting 14th, 13th, and 12th Gen Intel Core processors with R680E, Q670E,



and H610E chipsets. It offers up to 64GB DDR5 4800MHz memory, ensuring powerful performance for edge computing applications.

Optimised for AI-powered automation, self-service kiosks, smart signage, and transportation, it features dual 2.5GbE ports for fast networking, PCIe x16 Gen 5 slots, and versatile M.2 options for seamless integration. With support for four 4K displays and remote management via the M2-OOB module, it enhances operational efficiency, reduces downtime, and ensures scalability for evolving needs.

DFI

<https://www.dfi.com>

AC/DC power supplies

Traco Power's TXN series offers 50, 75, and 100-watt models, replacing the older TXL, TXM, and TXH lines while maintaining familiar design principles for a seamless transition. These com-



compact power supplies feature a low-profile metal enclosure and screw terminal

block for easy installation, catering to industrial setups. With an operating range from -40°C to +70°C, 3000V AC reinforced isolation, and built-in protection against short circuits, overvoltage, and overload, the series ensures safety and durability. Compliance with the industrial standards, combined with fanless convection cooling, makes it reliable, and cost-efficient for industrial use.

Traco Power

<https://www.tracopower.com/int>

Programmable resistor modules

Pickering Interfaces has launched new PXI (40-254) and PXIe (42-254) programmable resistor modules, the first in its range to support up to 2A



and 200V, with up to 15W power per channel. These

modules offer 1Ω to 395kΩ resistance, resolutions from 0.125Ω to 8Ω, and power handling options of 2.5W, 5W, and 10W. They feature 9-pin D-type connectors and support 1 or 2 resistance channels. Ideal for simulating resistive sensors and faulty wiring conditions, these modules provide 28 configurations.

Pickering Interfaces

<https://www.pickeringtest.com/en-us>

MANUFACTURING EQUIPMENT

3D AOI inspection system

Test Research Inc. (TRI) has introduced the TR7700QC SII, part of its core features 3D AOI lineup for