


solution. These DSCs feature a 32-bit CPU at 200MHz, double-precision floating-point unit (DP FPU), and DSP instructions, enabling efficient




control algorithms for motor control, power supply, charging, and sensing systems. Enhanced math and data processing,

reduced latency, and fast context switching improves transient and safety-critical event responses. With integrated 12-bit ADCs, comparators, operational amplifiers, and core independent peripherals (CIPs), these DSCs enhance real-time control and efficiency. Flash security features and model-based design support are ideal for motor control, digital power conversion, and sensor interfacing.

Microchip Technology
<https://www.microchip.com>

Compact CMOS op-amp

ROHM's TLR377GYZ is a compact CMOS operational amplifier between 1.8V and 5V, suitable for amplifying



sensor signals in temperature, pressure, and flow rate measurements in smartphones and

small IoT devices. It has low input offset voltage and ultra-low noise ensuring precise signal amplification. Housed in a WLCSP package, it is 69% smaller than traditional models. Key specifications include 1.8-5.5V power supply, 0.585mA/ch circuit current, 137dB voltage gain, and 25mA output current. An IC-mounted conversion board for SSOP6 packages

is also available for easy replacement and evaluation.

ROHM Semiconductor
<https://www.rohm.com>

Laser measurement sensors

Panasonic Industry's HL-G2 series expands its laser measurement sensors,



offering high accuracy with resolutions up to 0.5μm, linearity of $\pm 0.05\%$ F.S., and a 100μs sampling rate. An integrated controller simplifies product selection, reducing installation time and space. With EtherNet/IP communication, the sensors

output digital data directly, minimising conversion errors and optimising equipment control with high-speed sampling and real-time configuration.

Panasonic Industry
<https://industry.panasonic.eu>

Video decoding/encoding SoM

MYIR has introduced the MYC-LR3568, an affordable system-on-module (SoM) featuring the Rockchip



RK3568, a quad-core ARM Cortex-A55 processor that balances high performance with low power consumption.


Equipped with a Mali-G52 2EE GPU and supporting up to 1 TOPS NPU, the SoM excels in 4K 60fps video decoding and 1080P 60fps encoding. Compact in size, it includes 2GB LPDDR4 memory, 16GB eMMC storage, and a 381-pin LGA interface. Supporting Linux and Debian, it is ideal for IoT gateways, industrial control, and facial recognition. The

development board offers extensive peripherals, expansion options, and customisation.

MYIR
<https://www.myrirtech.com>

Non-isolated DC-DC converters

TDK Corporation introduces the RGB series, rugged non-isolated DC-DC converters rated from 400 to 750W, de-



signed for harsh environments.


Suitable for

medical devices, AGVs, IMRs, drones, COTS systems, and industrial applications, these converters deliver up to 750W within a compact 1/16th brick footprint. They offer high efficiency, adjustable output voltages from 0.8 to 24V, and input ranges of 9-60V, with output currents up to 60A. Operating temperatures range from -40°C to +115°C, and the converters are encapsulated to withstand shocks and vibrations per MIL-STD-810G standards, featuring a five-sided aluminium casing for reduced EMI and fanless operation.

TDK Corporation
<https://www.tdk.com/en>

NFC/RFID device

REYAX Technology has introduced the RYRR30D, an NFC/RFID device enhancing connectivity, security, and convenience.



Certified by Apple Wallet VAS and Google SmartTap, it ensures robust

compatibility. The device features NFC technology, Apple ECP V1.0 compli-



**WE LOVE TO
SHOWCASE
NEW PRODUCTS!**

Launched a New Product related to electronics?

Share its details with us at newproduct@efy.in
Send a photo too. We will be happy to review it, and if it matches our guidelines—we will publish it here, for FREE!