

Off-line converter

VIPer11 off-line converter with embedded 800V avalanche-rugged metal oxide semiconductor field-effect transistor (MOSFET) from STMicroelectronics enables equipment makers to design tougher auxiliary power supplies and power adapters. Its 26V DC drain-start voltage allows an ultra-wide line input voltage range. It enhances flexibility in numerous consumer and industrial applications.

The logic-level primary MOSFET enables VIPer11 to operate with a wide supply voltage range, from 4.5V to 30V, allowing the design of highly efficient 5V output switched-mode power supply. This advantage in combination with features like integrated high-voltage startup, error amplifier and jittered oscillator that reduces EMI, simplify design and save space and BOM costs.

STMicroelectronics India
www.st.com



Isolated power converters

Analog Devices announces its latest generation of reinforced isolated power converters. ADuM5020/6020 and ADuM5028/6028 series eliminate the need for costly electromagnetic interference (EMI) mitigation techniques at application level. These simplify EMI certification process, reducing design cost and time.

Product highlights include:

1. Low radiated emissions below class B EN 55022/CISPR 22 standard limits
2. Smallest package size of 8-lead small outline IC
3. High temperature operation at 125°C
4. Safety and regulatory approvals (UL, CSA, VDE, CQC)

Analog Devices Inc.
www.analog.com

Buck regulators

ON Semiconductor releases three new highly-efficient mid-voltage pulse width modulation (PWM) buck converters. Supporting a wide input voltage range of 4.5V to 65V, output current of up

to 10A and output power of 100W, the FAN6500X family of buck converters combines fixed frequency control scheme with flexible type III compensation and robust fault protection. ON Semiconductor has integrated its PowerTrench MOSFET technology to create a rugged integrated solution that delivers power density and efficiency for DC-to-DC applications.

ON Semiconductor
www.onsemi.com



MCU board

OpenMV Cam is a small, low-power, MCU board that allows easy implementation of applications using machine vision in the real world. It allows programming OpenMV Cam in high-level Python scripts (courtesy MicroPython operating system) instead of C/C++.

Important features are:

1. STM32F765VI ARM Cortex M7 processor runs at 216MHz with 512kB RAM and 2MB flash
2. OpenMV Cam records video and pulls machine vision assets off µSD card
3. OpenMV Cam comes with 2.8mm lens on standard M12 lens mount

Rajguru Electronics (I) Pvt Ltd
www.rajguruelectronics.com



TEST & MEASUREMENT

Multimeters

Flir DM62 and DM66 digital multimeters combine a rich feature set, precise measurements and quality construction into tools of exceptional value. The meters are easy to use and built to last, offering long-term stability for everyday use. These offer accuracy and range of measurement options for commercial electricians, automation field service professionals, electronics repair technicians and DIYers.

Key features are:

1. Measure both AC-to-DC voltage and current



2. Safely check voltage with non-contact voltage detection

3. One-hand usage, due to compact design and easy-access buttons

FLIR Systems India Pvt Ltd
www.flir.in

FTTx measurement kit

With FTTx measurement kit, Laser Components offers a complete package for control and acceptance measurements in FTTx and PON networks with wavelengths of 1310nm, 1490nm, 1550nm and 1625nm. This kit is specifically designed for companies involved in the broadband roll-out by Deutsche Telekom. It contains both ORL-85 and OLP-85 measuring instruments by Viavi Solutions, as well as all necessary patch cables and couplings.

Laser Components
www.lasercomponents.com



Safety tester

MI 3394 CE multi-tester XA is a portable instrument intended for electrical safety testing and CE certification of electrical appliances, machines and switchboards during production. Using metrel electrical safety manager, users can create custom test sequences and upload these to the advanced data management facility on the instrument.

MI 3394 provides Hi-Pot (0-5kV AC and 0-6kV DC) tests, state-of-the-art data management facility (memory organiser) and the ability to create multi-level test structures or sequences for fast and reliable execution.

NSM Technologies Pvt Ltd
www.nsmtechnologies.co.in



Oscilloscope

Rohde & Schwarz (R&S) introduces the high-performance R&S RTP family, expanding its portfolio to support up to 8GHz bandwidth oscilloscope. R&S RTP is ideal for debugging electronic

