



FEEDBACK

YOUR SUGGESTIONS

EFY JOURNAL

This is to bring to your kind notice that Parliament Library has been receiving copies of your esteemed periodical *Electronics For You* on complimentary basis for a long time, for reference and use of Members of Parliament. However, we have not received any issue since March 2016. It would be appreciated if you could arrange to supply the above-mentioned issues at the earliest, to enable us to maintain and update our holdings.

Simmi Moudgil, AD

Circulation Counter,
Parliament Library Building,
New Delhi

LOW-COST GPS CLOCK

'Simple and Low-Cost GPS Clock' DIY article published in July issue is interesting! Please let me know if the complete kit is available with you.

O. Subrahmanyam

Through email

EFY. Thanks for the feedback! The complete kit of a similar project based on Arduino is available at Kits'N'Spares. For details, please contact them at info@kitsnspares.com or visit their website, www.kitsnspares.com

TEMPERATURE ON SMARTPHONE

This is regarding 'Temperature Monitoring On Smartphone' DIY article published in July issue. How can I transmit temperature data from HC-05 Bluetooth module to my laptop to monitor temperature readings?

Kumaresen Annamalai

Through email

The author Shibendu Mahata replies: Data from smartphone can be sent to PC via Bluetooth of the smartphone. Receiver side should also have Bluetooth with Arduino, which reads data

and displays it on the serial monitor of Arduino.

PC-BASED OSCILLOSCOPE

In 'PC-Based Oscilloscope Using Arduino' DIY article published in June 2017 issue, I used Arduino Nano instead of Arduino Uno. When a known frequency is fed to input, correct waveform appears on the monitor. However, there are unexpected noise curves on the monitor in no-signal condition. Please help!

Md. Helal Kalimullah

Through email

The author Ramalingam Balaji replies: Connect a 100-kilo-ohm resistor between ADC pin and ground. This will suppress the noise when the pin is unconnected.

30W AUDIO AMPLIFIER

In '30W Audio Power Amplifier Using NE5534 And Darlington Transistors' DIY article published in November 2017 issue, how can I adapt it for a 4-ohm, 40W speaker?

Selva

Through email

The author Petre Tzv. Petro replies: You can connect 4-ohm, 40W speaker under the following restrictions:

1. Maximum current or $I_{max} \leq 5.0A$
2. Maximum power supply up to $\pm 25V$
3. Using appropriate heat-sinks for transistors with thermal resistance below $1.5^{\circ}C/W$
4. Using appropriate fast fuse rating
5. Using more powerful Darlington transistors (optional)

ARDUINO NANO BOARD

Arduino Nano board received against my subscription is not working. The driver software seems to be missing.

Suresh K.

Through email

From electronicsforu.com

Electronics Projects

In 'Virtual Telepresence Robot Using Raspberry Pi' article available on <https://electronicsforu.com>, can I use a single motor to move the camera in horizontal and vertical directions?

Minoy Aravindakshan

EFY. No! In this project, two motors are required to move the camera in these directions.

In 'RFID-Based Automatic Vehicle Parking System' available on <https://electronicsforu.com>, may I know the programming language for creating a similar project?

Zenogene

EFY. This project uses C programming language, but you can use other programming languages such as Python.

In 'Cellphone-Based Water Pump Remote Controller' project available on <https://electronicsforu.com>, can I use CM8870 instead of MT8870 DTMF decoder?

Amrathesh

EFY. Yes, you can use CM8870 in place of MT8870 DTMF decoder!

EFY. If you have the latest Arduino IDE on your Windows PC, you do not need a separate driver software—the system automatically detects Arduino. However, if you have old Arduino IDE or an old Windows PC, then you need a driver such as CH340. The same can be downloaded from <https://github.com/HobbyComponents/CH340-Drivers>

Download it, unzip the folder and install it on your system. Make sure you download the appropriate driver as per your Windows OS (32-bit or 64-bit).

After successful installation, connect Arduino Nano to your PC.