

OSCONIQ®P 3737



Product Key Features

- Long lifetime
- Maximum light output at minimized package size
- Enables very compact luminaire designs.
- 2 Watt version & 3 Watt version available

Applications

- Professional outdoor lighting (street- and tunnel lighting) Industrial luminaires (high bay, low bay)
- High mast lighting

OSLON®SQUARE



Product Key Features

- Ultra-compact footprint (3mmx3mm) for high density arrays to simplify circuit designs.
- Available with CRI 70,80,90
- Wide range of CCT selection
- Very low thermal resistance
- Superior robustness and long lifetime

Applications

- Street lighting
- Tunnel lighting
- Architectural lighting
- Low, high bay
- Path lighting

DURIS®S 8



Product Key Features

- Footprint: 5mm x 5mm
- Various luminous flux packages from one package family
- Small light emitting surface improves optical behavior in directional lighting.
- Optimized driver efficiency and costs due to higher voltage option.

Applications

- Directional lights for shops, hospitality and home
- Street light
- Consumer outdoor
- High luminous flux clusters, e.g. high bay lights
- Directional retrofits (e.g. MR16)

OSRAM Opto Semiconductors comes with decades of experience in a broad variety of LED application sectors as well as through its compliance with the highest quality standards. It is uniquely positioned to cover the whole range of LED technology needed in all Outdoor lighting sectors. You have the idea, we have the solution. Ask us at <https://www.ledlightforyou.com> or email us at prasias@osram-os.com.

Visit the products' webpage to read more : <https://www.osram.com/os/products/index.jsp>