



FEEDBACK

YOUR SUGGESTIONS

AUDIO AMPLIFIER

In '30W Audio Power Amplifier Using NE5534 and Darlington Transistors' DIY article published in EFY Nov. 2017 issue, connections between resistor R9 and diodes D3 and D4 seem wrong. Please check.

Viswesh

Through e-mail

The author, Petre Petrov replies:

There is no error in the circuit. Resistor R9 (150-ohm) is required to reduce total harmonic distortion in the circuit. The circuit may work if you remove this resistor but will give you very poor results.

LI-FI DONGLE

I have purchased the kit of 'Design Your Own Li-Fi Dongle and Speaker' DIY project published in July 2017 issue from Kits'n'Spares. After soldering components on the PCB, I am unable to understand where to connect the speaker. Do I need to solder the speaker to the solar panel?

Shraddha Bhujbal

Through e-mail

EFY. You cannot directly connect or solder terminals of the speaker to the solar panel. It is because the modulated sound signal transmitted by the Li-Fi dongle circuit and captured by the solar panel first needs amplification to be audible in the speaker. That is why you need a Li-Fi speaker as mentioned in the text.

Alternatively, you can use a speaker with an inbuilt amplifier having 'Audio in' socket. Then connect the solar panel output to an audio jack. Connect this jack to the speaker's Audio in socket.

During initial setup, keep transmitter (audio source + Li-Fi dongle circuit) and receiver (solar panel + speaker) units close to each other, say, about 30cm apart.

From electronicsforu.com

Electronics Projects

Thanks for 'Frequency Counter' circuit on your website at <https://electronicsforu.com/electronics-projects/frequency-counter>. I am trying to simulate it using Proteus software but without success. The circuit doesn't count. Please help.

Hazem Ayman

EFY. Thanks for the feedback! We have not tried it on Proteus software but it was working well on the breadboard. We suggest you to try it on either breadboard or PCB.

I liked the 'Audio Mixer with Multiple Controls' circuit given on your website <https://electronicsforu.com/electronics-projects/audio-mixer-multiple-controls>. Can I get the PCB layout in Altium software?

Meteorain

EFY. Thanks for the feedback! We only use gEDA software for circuit and PCB layout design.

In 'IoT Wi-Fi Temperature-Logging System' available on your website <https://electronicsforu.com/electronics-projects/pic-iot-wi-fi-temperature-logging-system>, what will be the output and where can we see the same?

Hassan

EFY. The output of the project is the temperature value being captured by the temperature sensor. It is shown on the LCD and also in the live temperature data graph on thingspeak.com website.

□ In the above-mentioned Li-Fi Dongle circuit, how can I connect a 3.5mm stereo jack at the receiver side? Can I use a 6.5mm mono connector on the transmitter side?

Simon Caldeira

Through e-mail

EFY. You can directly connect solar panel terminals (plus and minus) to the 3.5mm stereo jack. Then connect this jack to the 'Audio in' socket of the speaker. You can use any audio connector (mono or stereo) at the transmitter side depending on the audio source you have. You may go through 'Circuit and working' section of this article again for more details on Li-Fi dongle and speaker setup.

ARDUINO PROJECTS

Please send me the list of all Arduino projects published in EFY.

Aruna Sree Kannan

Through e-mail

EFY. We have been publishing many different projects based on Arduino since 2011. Arduino-based DIY articles published in 2017 are listed below along with month/issue:

1. Optical Thermo Musical Instrument Using Arduino Uno Board, December
2. DC Motor Soft Starter Using Arduino, December
3. Multi-LCD Using Arduino, November
4. Programming Arduino via Android Mobile Device Using Arduino-Droid, September
5. Arduino-based Smartphone-controlled Car, August
6. PC-based Oscilloscope Using Arduino, June
7. Arduino-based Windows PC Volume Remote Control, May
8. Duck Hunt using Arduino Uno and Python, March

Corrections

In eStyle Special Supplement of January issue, on page 24, under Buyer's Guide section, please read the title 'The Best Smart TV Within ₹ 3000' as 'The Best Smart TV Within ₹ 30,000'. The error is regretted.