



Server and Networking Power Supplies

AC-DC Distributed Power Front-Ends

- Common Form Factor
- Digital Control (PMBus®)
- 500 - 2000 W
- High Density and Reliability
- Market-Leading Efficiency
- AC and DC Input Options

495 W



DS495SPE

- 495 W Output Power
- 41.25 A max Output Current
- 3 A max Standby Output Current
- High Power Factor

500 W



DS500SDC

- 500 W Output Power
- (-48 V DC input)
- 41.76 A max Output Current
- 3 A max Standby Output Current

750 W



DS750PED-3

- 750 W Output Power
- 62.5 A max Output Current
- 3 A max Standby Output Current

550 W



CSV550BP

- 550 W Output Power
- 45.1 A max Output Current
- 2.5 A max Standby Current

900 W



CSV900BP

- 900 W Output Power
- 73.8 A max Output Current
- 2.5 A max Standby Current

1600 W



CSV1600BP

- 1600 W Output Power
- 131.2 A max Output Current
- 2.5 A max Standby Current

2000 W



CSV2000BP

- 2000 W Output Power
- 163.9 A max Output Current
- 2.5 A max Standby Current



Products Inquiry:

Tel.: +91 80 6743 1314

Email: powersales@artesyn.com

www.artesyn.com