

Double the Scope at Half the Price

- 100 & 200 MHz Bandwidth
- 1 GSa/s Real-time Sampling Rate
- Measurements and Math Applied to All Memory Samples
- 1 M Points FFT
- Serial Bus Triggering and Decoding (Standard)
- **Bode Plot Function. Options for Remote AWG, WiFi, and 16-Channel Digital Channels (MSO)**

SDS1000X-E Series Super Phosphor Oscilloscope **Four-Channel**

NEW!



Models and key Specification

Model	SDS1104X-E	SDS1204X-E SDS1202X-E
Bandwidth	100 MHz	200 MHz
Sampling Rate (Max.)	Two channel series have a single 1 GSa/s ADC, four channel series have two 1 GSa/s ADCs. When all channels are enabled, each channel has a maximum sample rate of 500 MSa/s. When a single channel per pair is active, that channel has sample rate of 1 GSa/s	
Channels	4 (four channel series) 2+EXT (two channel series)	
Memory Depth (Max.)	7 Mpts/CH (not interleave mode); 14 Mpts/CH (interleave mode)	
Waveform Capture Rate (Max.)	100,000 wfms/s (normal mode), 400,000 wfms/s (sequence mode)	

Better Units For Lower Price

SDG6000X Series Pulse/Arbitrary Waveform Generator

500MHz

- Frequency up to 500 MHz
- EasyPulse & TrueArb Technology
- Sampling Rate up to 2.4 GSa/s
- I/Q Signal & PRBS Generator

NEW!

