

Surge protectors

RECOM's RSP-168 surge protectors allow DC-to-DC converters to meet both RIA12 and NF F 01-510 surge immunity specifications for railway applications. The surge protector modules protect railway DC-to-DC converters from excessive voltage surges up to 385V DC. Output voltage tracks input voltage up to 165V DC. Thereafter, output voltage is clamped to prevent damage to the converter from input over-voltage conditions that cannot normally be filtered out.

RECOM Asia Pte Ltd

www.recom-power.com



Phototransistor optocoupler

Vishay Intertechnology has launched its first automotive-grade phototransistor optocoupler, VOMA617A. The device combines high current transfer ratio with low forward current of 5mA in the compact SOP-4 mini-flat package. This saves 30 per cent PCB space compared to DIP-4 package. VOMA617A is designed for galvanic and noise isolation, signal transmission, battery management and system control in automotive applications, including hybrid and electric vehicles, as well as high-reliability industrial applications.

Vishay Intertechnology Inc.

www.vishay.com



Buck regulators

Texas Instruments has introduced two wide vin-synchronous simple switcher DC-to-DC buck regulators in ultra-small HotRod quad-flat no-lead (QFN) packaging. The highly-integrated 3-A LMR33630 and 2-A LMR33620 step-down voltage converters feature a full load efficiency—92 per cent—for rugged and reliable industrial power supplies with switching frequencies up to 2.1MHz.



The small HotRod QFN package includes unique wettable flanks, enabling post-solder optical inspection to simplify manufacturing. This gives LMR33630 0.5A/mm² power density at 3A of current.

Texas Instruments

www.ti.com

Synthesizer

Analog Devices has launched a state-of-the-art synthesizer consisting of a phase-locked loop with fully-integrated voltage-controlled oscillator as well as integrated low dropout regulators and integrated tracking filter technology. ADF4371 supports radio frequency/microwave system designs that must meet next-generation requirements across multiple sectors, including aerospace and defence, test and measurement, communications infrastructure as well as high-speed converter clocking.

Analog Devices Inc.

www.analog.com

DC-to-DC converters

MORNSUN's fixed input voltage DC-to-DC converters, R3 series, adopt IC technology to decouple conflict among continuous short-circuit protection, capacitive load and start-up capability to get the three performances promoted, simultaneously. The converters facilitate customers' system upgrade with compatible designs.

Mornsun Guangzhou Science & Technology Co. Ltd

www.mornsun-power.com



Oscillators

Ultra-small and lightweight 32.768kHz oscillators—OM7605C8 and OV7605C8—feature 2.0 x 1.2mm foot print, have excellent frequency tolerance, operate over -40 to +85°C and are available with optional AEC-Q200 qualification.

OM7605C8 has a metal lid and height of 0.7mm. Featuring a mass of only 5.1mg, this oscillator is perfect for weight-sensitive



applications, including aerial tracking and drone applications.

OM7604C7 comes in a ceramic package with metal lid. It offers significant savings over current 32.768kHz solutions. It is available with extended -40°C to +125°C operating temperature range.

Golledge Electronics

www.golledge.com

TEST & MEASUREMENT

UV-light meter

Techsil has launched an ultraviolet (UV) meter from UV curing equipment specialists, Hönle. The meter measures intensity and dose of UV and UV LED curing units and systems. It has a wide range of interchangeable sensors, covering wavelengths from 230nm to 550nm—UVA, UVB, UVC and VIS—that makes it suitable for different manufacturing processes. Its compact sensors are 14mm high to fit into small spaces. Two-channel measuring means different wavelength ranges can be recorded at the same time.

Techsil Ltd

www.techsil.co.uk



Bare board testing machine

M.S.B. Electronics has introduced a bare board testing machine from Utron Technologies Corp., Taiwan. UT8008HV6 can test up to maximum 4096 test points, at a super speed of 2048 test points/ per second. It can perform tests like continuity, leakage, insulation and current in just one operation. It offers a test area of 450mm x 320mm.

M.S.B. Electronics

www.msbelectronics.com



Compliance test solution

The test solution by Anritsu comes with multi-vendor oscilloscope support and can be used for both PCI Express