

transmitter and receiver tests using automation software for MP1900A. In addition, it enables connection of customers' oscilloscopes with MP1900A by supporting real-time oscilloscopes from three main manufacturers, permitting automation of complex receiver tests required for evaluating devices in accordance with PCI Express standards. Automated testing lightens the workload burden on test engineers by cutting the previous 10 hours required for manual testing to almost no time.

Anritsu India Pvt Ltd
www.anritsu.com

Oscilloscope

Rohde & Schwarz has announced R&S RTP oscilloscope with a fast acquisition rate of one million waveforms, which can help users find sporadic errors faster per second. The oscilloscope compensates transmission losses from the signal source to the oscilloscope (de-embedding) in real time, making the device faster even after activation of signal correction. With digital trigger architecture, it can precisely trigger on compensated signals.

Rohde & Schwarz
www.rohde-schwarz.com

INTERNET OF THINGS

Security chip

STMicroelectronics has brought together latest digital security techniques in a single chip to protect smart things and networks, including those for utility infrastructure, against cyber threats. Focused on providing state-of-the-art security for connected objects, STSAFE-J100 gives the object an unalterable identity that can be authenticated. It handles encrypted communications and provides secure storage. It is easily integrated in Internet of Things (IoT) devices like smart meters, data concentrators and utility gateways. Customisable with market-specific applets, STSAFE-J100 secure element combines CC EAL5+ certified hardware and CC EAL5+ certified secure operating system.

STMicroelectronics India
www.st.com

Wireless module

HLK-M50 - SUIT v1.2 is compatible with NodeMCU ESP8266 LUA Wi-Fi Internet module ESP 12E development board. Features of WLAN are:

- Single-chip integrated MAC/PHY/radio, integrated PA, LNA
- Supports 2.4GHz IEEE 802.11b/g/n; 20/40MHz bandwidth, maximum 150Mbps
- Supports WPA, WPA2, WEP, TKIP and CCMP
- Supports STA, softAP, P2P, STA + softAP, STA + P2P, A-MPDU, A-MSDU and HT-BA
- Features lightweight TCP/IP protocol stack

Rajguru Electronics
www.rajguruelectronics.com



MISCELLANEOUS

Fluid dispensing robot

Nordson EFD has introduced a vision-guided GV Series automated fluid dispensing gantry robot. Specialised DispenseMotion software and an integrated CCD smart vision camera or simple pencil camera make the automated systems quick to set up and easy to program. The CCD camera converts pixels into digital values to deliver precise, high-quality images. The proprietary dispensing software confirms workpiece presence and placement, and automatically adjusts as in-process variations occur.

Nordson India Pvt Ltd
www.nordson.com



Programmable bell driver

Perfect Electronics has developed a programmable bell driver for colleges and schools. It includes a built-in clock. Maximum 36/64 timings can be fed to the unit. During mains failure, UPS-cum-EPS of 500V A can be



used with this system, so that the bell rings during mains failure, too. The system can be used as a home security system or an electronic watchman (night timings can be fed).

Perfect Electronics Pvt Ltd
www.perfectelectronics.com

Development environment

Renesas Electronics has announced an update to its embedded target for RH850 multi-core model-based development environment for multicore MCUs for automotive control applications. The update supports development of systems with multi-rate control (multiple control periods), which is now common in systems such as engine and body control systems.

Renesas Electronics Corp.
www.renesas.com

Electroluminescent display

LINEPRO has introduced electroluminescent (EL) technology by printing phosphor on a polyester sheet. This thin, flexible and uniform light is suitable for applications like backlite for front panel in electronic instruments. Since it is screen printable, it can be customised as per application. Each printed light segment can interface with an MCU, so it is possible to create light animation with EL technology.

Linepro Controls Pvt Ltd
www.lineproindia.com



Power supply

SPD1168X programmable linear DC power supply has a 7.1cm (2.8-inch) TFT-LCD display, remote computer control capability and real-time wave display, for delivering high performance and ease-of-use. It features a high-precision programmable output capable of delivering up to 16V. It also includes a 4-wire sense function for more accurate voltage sourcing, especially for long leads or high-resistance connections.

Siglent Technologies Co. Ltd
www.siglent.com

