

Small in Size Big on Features

SPD1168X Series Programmable DC Power Supply

- Single Output: 0 – 16 V / 8 A
- Low Ripple; Fast Response
- Four-Wire Compensation (Sense) Function
- Resolution of up to 1 mV / 1 mA



Double the Scope at Half the Price

SDS1000X-E Series Super Phosphor Oscilloscope

2/4 Channel

- 100 & 200 MHz Bandwidth
- 1 GSa/s Real-time Sampling Rate
- Measurements and Math Applied to All Memory Samples
- 1 M Points FFT
- Serial Bus Triggering and Decoding (Standard)
- Bode Plot Function. Options for Remote AWG, WiFi, and 16-Channel Digital Channels (MSO)



Models and key Specification

Model	SDS1104X-E	SDS1204X -E SDS1202X-E
Bandwidth	100 MHz	200 MHz
Sampling Rate (Max.)	Two channel series have a single 1 GSa/s ADC, four channel series have two 1 GSa/s ADCs. When all channels are enabled, each channel has a maximum sample rate of 500 MSa/s. When a single channel per pair is active, that channel has sample rate of 1 GSa/s	
Channels	4 (four channel series) 2+EXT (two channel series)	
Memory Depth (Max.)	7 Mpts/CH (not interleave mode); 14 Mpts/CH (interleave mode)	
Waveform Capture Rate (Max.)	100,000 wfm/s (normal mode), 400,000 wfm/s (sequence mode)	