

requirement of external capacitors. The product family consists of 14 models with output voltages ranging 1.2 ~ 15V DC. All models are tightly regulated and operate with one per cent load variation from 0 ~ 100%, overload protection and extreme reliability exceeding 13 million hours per MIL-HDBK-217F.

Traco Power
www.tracopower.com

Cartridge fuses

Littelfuse introduces the smallest cartridge fuse series available that are rated at 500V AC with current ratings from 40A to 63A and 2000A at 500V AC interrupting rating. The 606 series high-current cartridge fuse is designed for overcurrent protection in applications such as high-voltage power supply circuits rated up to 23kW. With a 10mm x 32mm cartridge body, a single 606 fuse requires less board space than previous designs that used multiple lower current rated fuses in parallel.

Littelfuse Inc.
www.littelfuse.com/

IGBT diode

Infineon Technologies launches a new diode family especially designed for modern insulated-gate bipolar transistor (IGBT) applications, Infineon Prime Soft. These diodes feature an improved turn-off capability that rates at 5kA/μs. Typical applications for the diodes include HVDC/FACTS and medium voltage drives using voltage source converters. These applications are marked by demanding requirements on power losses.

Infineon Technologies India Pvt Ltd
www.infineon.com

Regulator

Analog Devices announces Power by Linear LTM4661, a low-power step-up μModule regulator in a 6.25mm x 6.25mm x 2.42mm BGA package. Only a few capacitors and one resistor are required to complete the design, and the solution occupies less than 1cm² single-sided or 0.5cm² on double-sided PCBs. LTM4661 incorporates a switching DC/DC controller, MOSFETs, inductors and

supporting components. It operates from a 1.8V to 5.5V input supply and continues to operate down to 0.7V after start up. Output voltage can be set by a single resistor ranging from 2.5V to 15V. The combination of the small, thin package and wide input and output voltage range is ideal for a wide range of applications including optical modules, battery-powered equipment, battery-based backup systems, bias voltage for power amps or laser diodes and small DC motors.

Analog Devices Inc.
www.analog.com

EQUIPMENT

Thermal imaging camera

The entry-level E53 advanced thermal imaging camera offers superior resolution and range performance needed to quickly identify hot spots and discover potential points of failure in electrical distribution and mechanical systems. With 43,200-pixel resolution and a vibrant LCD screen, E53 makes it easier to diagnose problems, even from a distance. Avoid costly shutdowns and lost production time through regular predictive maintenance routines and improve plant reliability and safety with this rugged, intuitive camera.

FLIR Systems India Pvt Ltd
www.flir.in

Solder paste jetting system

Nordson EFD introduces Liquidyn P-Jet SolderPlus jet valve and solder paste system. This non-contact jetting system is designed specifically to jet Nordson EFD SolderPlus dispensing paste with high accuracy and repeatability. The system eliminates the need for Z-axis movement. This allows for significantly faster production speeds when compared to contact dispensing. It also makes it easy to dispense solder paste consistently onto uneven surfaces or parts with varying tolerances.

Nordson India Pvt Ltd
www.nordson.com

PoE switches

Moxa launches EDS-P506E-4PoE series of PoE switches that can provide up to 60W per PoE port for converged data and power transmission. The power output is designed for IP cameras that use power-demanding functions such as PTZ, illumination, heaters and fans in harsh environments. The switches feature device-level cyber security, remote control and the capability to monitor powered devices to meet the operational requirements for industrial applications such as highways, wayside and public utilities.

Moxa India
www.moxa.com



MISCELLANEOUS

Breakout board

Recom releases a breakout board to connect SensorTile from STMicroelectronics to RECOM's R-78S evaluation board. This technology enables SensorTile to draw a stable 3.3V from an AA battery down to voltages as low as 0.65V. Engineers can therefore integrate a high-capacity single-cell AA battery into their designs and use test points to estimate the application's operation lifetime.

Recom
www.recom-power.com



Starter kit for embedded applications

Mistral Solutions announces the release of 820 starter kit, a low-cost development platform for imaging applications built around Qualcomm Snapdragon 820E embedded platform. Based on a dual board architecture, 820 starter kit consists of Mistral's 820 Nano SOM and a compact carrier board that provides access to interfaces such as USB over Type-C and camera.

Mistral Solutions
www.mistralsolutions.com