



A101

Smallest sensor, ideal for OEM applications



A201 & HT201

Most popular sensor, capable of measuring in environments as hot as 200°C



A301 & ESS301

Standard 25 mm sensor with high temperature and humidity capabilities



A401

Largest circular standard sensor



A502

Largest square standard sensor (50.8 mm x 50.8 mm sensing area)



BONENS POTENTIOMETER



3296W-1-101LF 3296W-1-103LF
3296W-1-201LF 3296W-1-203LF
3296W-1-501LF 3296W-1-104LF
3296W-1-102LF 3296W-1-204LF
3296W-1-202LF 3296W-1-504LF
3296W-1-502LF 3296W-1-105LF

3386P-1-101LF 3386P-1-103LF
3386P-1-201LF 3386P-1-203LF
3386P-1-501LF 3386P-1-104LF
3386P-1-102LF 3386P-1-204LF
3386P-1-202LF 3386P-1-504LF
3386P-1-502LF 3386P-1-105LF

Professional Receipt Printing Solution

PRINTER MECHANISM

All type of Printer Mechanism available as per customised requirement

1st Thermal Printer
Mechanism RT105RG



2nd Thermal printer
Mechanism RT628RG



3rd Thermal Printer
Mechanism RT638RG



Application:

Pos Machine
Billing Machine
Taxi Meter



Pos Machine



Billing Machine

Application: - Pos Machine - Billing Machine - Taxi Meter

HLK-8266

Product Features

esp8266 solution Support AiCloud/ airkiss/Private Cloud and so on
Support UART/GPIO/WIFI Support STA/AP/AP+STA work mode Airkiss
APP provide Support online firmware upgrade, provide wireless batch
configuration tools 3.3V $\pm$ 0.3 Single Supply Operation Size: 24mm x 16mm



HLK-M50

Product Features

- Integrated with MCU, PMU, clock and IEEE802.11b/g/n MAC/PHY/radio, etc./RDA5981 chipset solution
- Support USB Host and Device 2.0 HS, Micro SD card (SDMMC interface), UART, I2C, I2S, PWM, SPI, etc. support the simulation (GPADCO)
- Supports 20/40MHz bandwidth, up to 150Mbps
- Support online firmware upgrade, provide wireless batch configuration tools
- Support STA/AP work mode
- Support secondary development, customer can use C or C++ to develop their own firmware based on mbedOS
- Airkiss APP Provide
- 3.3V $\pm$ 0.3 Single Supply Operation
- Size: 24mm x 16mm



HLK-ESP32

Product Features

- Support 802.11b/g/n/ee wireless standard /esp32 solution
- Integrate with traditional Bluetooth, Bluetooth low energy, Wifi
- Supports capacitive touch sensors, Hall sensors, low-noise sensor amplifiers, SD card, Ethernet, high-speed SDIO/SPI, UART, PWM, I2S, ADC, DAC, and I2C
- Support for two CPU cores can be controlled individually, Clock frequency adjustment from 80 MHz to 240 MHz
- Supports 20/40MHz bandwidth, up to 150Mbps
- Support A-MPDU and A-MSDU aggregation, support 0.4 s guard interval
- Support STA/AP/STA+AP/2P
- Support UART download / wireless upgrade (OTA)
- Supports IPv4, IPv6, SSL, TCP/UDP/HTTP/FTP/MQTT network protocols
- Support AT+ instruction set, cloud server, Android/iOS app user configuration
- 2.7V to 3.6V Single Supply Operation
- Size: 18 $\pm$ 0.2 mm x 25.5 $\pm$ 0.2 mm x 2.8 $\pm$ 0.15 mm



Wide Range of LCD Display Module

CUSTOMIZED COLOUR ALSO AVAILABLE



RG1602 Blue



RG1602 Green

Features:

- 16 Characters x 2 Lines
- 5x7 Dot Matrix Character Cursor
- Works with almost any Microcontroller



RG2004 Blue



RG2004 Green

Features:

- High-Quality 4 line 20 character LCD Module
- Easy to Interface with most Micro Controllers



RG12864 Blue



RG12864 Green

Features:

- 128x64 Liquid Crystal Display
- Ideal for Moving Displays & Graphics
- Alphanumeric Characters
- Built-in Controller

Introducing CREC crystals in india



495 & 495L, 495MD & 495MG Quartz Crystal Resonators



SMD Crystal Oscillator (XO) 7050/5032/3225



SMD7050/5032/
3225/2520/2016