

Professional Electrical Testing Solution Provider

With 30 Years Experience of R&D, Manufacturing and Service



Microwave Safety iTest Solutions

- **UL Standards Compliance test:** 500VA Hi-Pot Output Capacity.
- **Multi-point grounding test:** Remote stick remote starter, up to 50-step test
- **High Precision:** The main parameters Accuracy 1%.



Information Products Quick Test Solution

- **Patented technology:** ground and voltage / insulation parallel test, a test to save time
- **Patented technology:** three-terminal safety scanning test the primary / secondary / housing for adapter, PC power supplies, inverters and other products tested;
- **Standby power test:** power parameter accuracy of 0.2%, the smallest current measurement 2mA, minimum power measurement 0.5W.



Quick appliances production line testing solution

- **Parallel Test:** Ground support and pressure / insulation parallel test; dynamic leakage power parameter test synchronization, save time.
- **Duplex test:** unique intelligent parallel mode, duplex synchronous test, a piece of equipment is higher than the two test speeds.

Standby power test: power parameter accuracy of 0.2%, the smallest current measurement 2mA, minimum power measurement 0.5W.



	Parameter Description
Test Project	[ACW / DCW Test]
Output	DC 0.10~6.00kV, AC : 0.10~5.00kV
Test Project	[IR Test]
Output	DC 0.10~2.50kV
Test Project	[GB Test]
Output current	AC : 2~32A
Test Project	[TC Test], [Run Test]
Touch Current Range	0~12.00mA
Meet the entry criteria	UL 544 NP, UL 544 P, UL 1563, UL60601-1, IEC60601-1, UL 3101-1, UL/IEC 60950, UL 1950-UI1*, UL 2601-UI*, IEC60990, IEC60335
Load current range	0~20.00Amp

Ainuo
Exceeding & Trustworthy

Ainuo Instrument Co., LTD.

Add: No.134 Zhuzhou Road, Qingdao, China, Tel: +86-532-83995118

E-mail: grace@ainuo.com service@ainuoworld.com

Web: <http://www.ainuoworld.com>