

fuse prevents electronic equipment used in hazardous locations from overheating or producing sparks that could ignite a fire or explosion, by minimising the risk of overcurrent/short-circuit events.

PICO 242 series fuse meets the requirements of intrinsic safety standards (IEC/EN/UL 60079-11) for hazardous location and explosive atmosphere applications. So products designed with it will follow relevant European directives and other global requirements.

Littelfuse Inc.

www.littelfuse.com

Power controllers

Infineon Technologies is launching a new generation of multichannel SPI high-side power controllers SPOC. This product family is used for multichannel high-side smart switches in automotive exterior lighting applications. The SPOC series is designed to address interior and exterior lighting applications but also power distribution applications such as door lock and seat heating, as well as lighting and power distribution loads for e-bikes.

Infineon Technologies

www.infineon.com

Amplifier

Texas Instruments has introduced a reinforced isolated amplifier that features precision and working voltages, and lifetime reliability. With exceptional performance that includes better nonlinearity, lower offset and gain error, and higher temperature stability, ISO224 allows engineers to overcome performance limitations and design high-precision systems. The amplifier is designed for isolated voltage sensing in factory automation and control, grid infrastructure, rail transport and motor drive applications.

Texas Instruments

www.ti.com

Buck boost controller

Analog Devices has announced Power by Linear LT8708/-1, a 98 per cent efficient bi-directional buck boost switching regulator controller that operates between two batteries that have the same voltage, which are ideal for redundancy in self-

driving cars. LT8708/-1 operates from an input voltage that can be above, below or equal to output voltage, making it well-suited for two each 12V, 24V or 48V batteries commonly found in electric and hybrid vehicles. It operates between two batteries and prevents system shutdown should one of the batteries fail. LT8708/-1 can also be used in 48V/12V and 48V/24V dual-battery systems.

Analog Devices Inc.

www.analog.com

TEST & MEASUREMENT

Mixed-signal oscilloscope

Rigol has introduced MSO/DSO 7000 series, which is six instruments integrated into one—4-channel digital storage oscilloscope, 16-channel logic analyser, 2-channel 25MHz arbitrary waveform generator, digital voltmeter, frequency counter



and protocol analyser. It has four USB host ports, one USB device port, LAN, HDMI interface and Web remote control, providing flexibility for controlling and monitoring.

Scientech Technologies Pvt Ltd

www.scientechworld.com

SOFTWARE

Signal generation software

Anritsu has launched 5G NR TDD sub-6GHz IQproducer MX370113A and 5G NR TDD sub-6GHz IQproducer MX269913A software packages, extending the company's line of measurement software for 5G mobile communications systems. Installing these software packages in vector signal generator MG3710A or signal analyser MS2690A/MS2691A/MS2692A series with installed vector signal generator Opt-020 supports output of 5G signals in the sub-6GHz frequency band.

Anritsu India Pvt Ltd

www.anritsu.com

5G toolbox for MATLAB

MathWorks has introduced 5G toolbox, which provides standards-compliant

waveforms and reference examples for modelling, simulation and verification of the physical layer of 3GPP 5G NR communications systems. Engineers using 5G toolbox can quickly design critical algorithms and predict end-to-end link performance of systems that conform to 5G release 15 standard specification.

MathWorks

www.mathworks.com

Design environment

WestDev has announced the next level of progression in its Pulsonix product with the release of version 10.0. The latest release of Pulsonix expands its product portfolio with intelligent interactive editing within the 3D design environment. By enabling co-design of the PCB within 2D PCB and 3D environments, Pulsonix shortens the time-to-market with a more productive workflow and reduces costly errors.

The new interactive 3D design environment is complemented by new interactive functionality, enabling dynamic copper pouring and shape healing. Automatic pad style naming has also been introduced to ensure maximum efficiency.

Hapstronics Technology Pvt Ltd

www.hapstronics.com

INTERNET OF THINGS

IoT starter kits

ESP32 MCU-based Internet of Things (IoT) starter kits from M5Stack are modular, stackable and Arduino-compatible design solutions, which come with ESP32 Wi-Fi + BLE modules, 16MB flash, 4MB PSRAM, colour LCD, batteries, speaker and other peripheral components required to start and finish a project faster.



Unlike traditional development boards, here the development board is already built into an enclosure with a graphical display, push buttons, microSD card slot, USB-C, loudspeaker, and extension connectors. The prototype becomes a final product at the end of design phase.

Uchi Embedded Solutions

sales@uchiembedded.co.in