




Creative Ideas Infinite Possibilities

Technical supports of performance, price and profession for accelerated product design and development.

Introducing Holtek's new 96 MHz high performance and low power consumption Arm® Cortex®-M3 based Flash microcontroller devices with 3.3V and 5V wide voltage ranges respectively. This new series with their higher operating speed and abundant high performing hardware resources provide superior and flexible solutions for more demanding embedded system designs. The HT32 Cortex™-M3/M0+ families will find applications in a wide variety of products, in areas such as IoT terminal devices, USB gaming peripherals, fingerprint recognition products, TFT-LCD displays, three-phase motor control, industrial control, home automation products, health care products, consumer electronics and so on. These devices provide users with a high level of functional integration and innovation advantages, implementing a superior product combination of performance, price and profession. These features combine to ease the path for rapid product development allowing fast entry into competitive product markets.



MCU Core

Arm® Cortex®-M0+/M3
20 ~ 96 MHz



Interface

UART, USART, SPI,
I²C, I²S, USB 2.0 FS



Timers

Timers for Capture, BFTM, PWM or
Complementary PWM, RTC, WDT



Memory

16 ~ 256 KB Flash
4 ~ 128 KB SRAM



Analog

12-bit 1 Msps ADC, VREF
Comparators, 12-bit DAC



Specific Features

AES, CRC, EBI, PDMA, Smart
Card I/F, SDIO, CMOS Sensor I/F, DIV

