

Disclaimer

The project report may be modified/tailored to suit individual entrepreneurship qualities/capacities, production programmes and location characteristics, wherever applicable.

turer rates a resistor at 50ppm/°C, the resistor will not change more than 50Ω in resistance for each 1MΩ of the resistor's given value, for a temperature change of 11°C. Typical alloys that are used as resistor wire are copper, silver, nickel-chromium, iron-chromium and iron-chromium-aluminium. Properties of the most common alloys are given in Table I.

Following raw materials are required for wirewound resistors:

- Viterous enamel/silicon-based resin
- Strips
- Resistance wires
- Caps and beads
- Consumables like hardener, rubber sheet and packaging

Machinery and equipment required are:

- Toggle action press of ½-ton capacity
- Automatic coil winding machine
- Lead cutting machine grinder
- Lead straightening machine
- Lead tinning machine
- Spot welding machine
- Oven (temp.)
- Stirrer (ball mills)
- LCR - Q meter
- Digital temperature indicator
- 4½-digit bench micro-ohm meter
- Dimmer stat (4A)
- 4½-digit digital multimeter
- Load tester and brake tester
- Fusing tent machine
- Tension tester
- Marking machine with accessories
- Resistance oil standards

Financial analysis

Table II shows fixed capital, that is, land and building, and machinery and equipment. Table III shows the cost of working capital per month.

Total capital investment is given in Table IV. Cost of production per annum is shown in Table V. Turnover per annum is shown in Table VI.

$$\text{Profit before taxes} = \text{Turnover per annum} - \text{Cost of production per annum} \\ = 7,200,000 - 5,839,184 = ₹ 1,360,816$$

$$\text{Profit ratio} = \frac{\text{Profit per annum} \times 100}{\text{Sales per annum}} \\ = \frac{1,360,816 \times 100}{7,200,000} = 18.90\%$$

EFY

References

1. www.physics-and-radio-electronics.com
2. www.resistorguide.com
3. www.dcsmc.gov.in
4. www.transparencymarketresearch.com
5. www.resistorguide.com
6. www.resistorguide.com
7. www.resistorguide.com
8. www.dcsmc.gov.in

BINAY - Lighting Up The Future



BINAY LED-based HIGH, MEDIUM and LOW Intensity Aviation Obstruction Light Beacons

As per International Civil Aviation Organisation (ICAO) requirements Available in Low Intensity, Medium Intensity and High Intensity versions (as per International Civil Aviation Organization guidelines), BINAY's patented LED Aviation Lights come with 5-year/3-year warranties

LED Obstruction Lighting for:

- Industrial chimneys and smokestacks
- Transmission, microwave and cellular towers
- Radio, TV and similar structural towers
- High-rise buildings and structures
- Airports and airfields

The BINAY LED Aviation Obstruction Light offers the following advantages:

- Fit-and-forget maintenance-free operation
- A long life of 100,000 hours (20 years at 12 hours daily burning)
- Pays for itself within a short period of operation in the form of reduced installation, maintenance and servicing costs
- Quick Installation; Reliable operation 365 days per year
- Shock-proof and vibration-resistant
- Over-Designed Intensity to allow for natural LED intensity degradation over its operating lifetime



THE BINAY LED OBSTRUCTION LIGHT IS UNDER ACCEPTED PATENT, AND AS SUCH IS A PROPRIETARY PRODUCT



Binay Opto Electronics Pvt. Ltd.

27, PANDITIA TERRACE, Calcutta 700 029, India
Telephone: +91 (33) 4006 9875, 2475 0392, 2475 0030
email : info@binayled.com, http://www.binayled.com

POWERING LED TECHNOLOGIES WORLDWIDE SINCE 1983