

NebuLink Gateway

A key **component** for **IoT** Infrastructure

SLS has been driving the path in IoT industry offering a diverse range of IoT Gateways which has the capability to speak with smart products having a wide array of communication protocol including Zigbee, 6LoWPAN, Bluetooth or G3-PLC and connect them to the Cloud using Wi-Fi, Ethernet or Cellular connectivity. NebuLink Gateways comes with fully supported open-source Yocto based Linux and FreeRTOS platform running on the latest processor, with pre-integrated stack support which makes it zero configurable platform.

Low Cost
and
easy to use

	NLG1100	NLG1200	NLG1300	NLG2200	NLG5100
Processor & CPU Frequency	Dual Core Xtensa® 32-bit LX6 upto 240MHz	Dual Core Xtensa® 32-bit LX6 upto 240MHz	Dual Core Xtensa® 32-bit LX6 upto 240MHz	Dual Core Xtensa® 32-bit M4 upto 80MHz	Multi Core ARM® Cortex-A5 & Cortex-M4 upto 500MHz(A5) & 167MHz(M4)
Internal/External RAM	~300KB/4MB PSRAM	~300KB/4MB PSRAM	~300KB/4MB PSRAM	64KB/512KB	1MB On Chip RAM/ 256MB DDR3
Connectivity	Zigbee/6LoWPAN, Wi-Fi, Bluetooth	Zigbee/6LoWPAN, Wi-Fi, Bluetooth	Zigbee/6LoWPAN, Wi-Fi, Bluetooth, 2G/3G/4G, GPS	Zigbee/6LoWPAN, Ethernet, 2G/3G/4G, GPS	Zigbee/6LoWPAN or 2G/3G/4G, Ethernet, GPS
Security	AES-encrypted TCP-based binary protocol for E2E data	AES-encrypted TCP-based binary protocol for E2E data	AES-encrypted TCP-based binary protocol for E2E data	AES-encrypted TCP-based binary protocol for E2E data	AES-encrypted TCP-based binary protocol for E2E data
Application	Smart Cities, Smart Homes	Smart Cities, Smart Homes	Smart Cities, Smart Homes	Industrial	Industrial

Contact us at +91 2692 232501(ext. 47) or Write to us at sales@slscorp.com



For Documentation
Scan QR Code or visit
<http://www.slscorp.com/marcom.html>

NEBULAE
DESIGN TO CONNECT
nebulae.io

Powered By

