



FEEDBACK

YOUR SUGGESTIONS

DIGITAL WEIGHING MACHINE

The 'Build Your Own Digital Weighing Machine' DIY article published in June issue is a nice project!

Kunal

Through email

EFY. Thanks for the feedback!

HIGH-VOLTAGE GENERATOR

The 'High-Voltage Generator for Microcontroller' DIY article published in August issue is really good!

Worapop Khawhlueng

Through email

❑ The 'High-Voltage Generator for Microcontroller' is a useful circuit. Thanks for publishing the same!

C. Govindan

Through email

❑ In 'High-Voltage Generator for Microcontroller' DIY article, it is mentioned that NE555 timer is configured as an astable multivibrator oscillator, which oscillates at a frequency determined by the values of resistors R1, R2 and capacitor C1. What is the formula to find oscillator frequency?

Gireesh Kumar

Through email

EFY. Thanks for the feedback! The formula for the astable multivibrator to find output frequency (f) is:

$$f = 1.443 / (R1 + 2 \times R2) \times C1$$

As per the published circuit, R1 is 1000-ohm, R2 is 10,000-ohm and C1 is 1nF.

PC-BASED OSCILLOSCOPE

In 'PC-Based Oscilloscope Using Arduino' DIY article published in June 2017 issue, how can we save the output waveform shown on the screen?

R. Srinath

Through email

EFY. You can take screenshots of the waveform data and save these on your computer.

BIKE TURNING INDICATOR

This is regarding 'Automatic Bike Turning Indicator' DIY circuit published in July issue. Does the indicator switch off automatically after turning?

Ankit

Through email

EFY. No! The indicator will turn off only when the bike's handle becomes straight.

VIRTUAL TELEPRESENCE

What is the approximate cost of making 'Virtual Telepresence Robot Using Raspberry Pi' based on the DIY article published in March issue?

Sumer Singh

Through email

The author Shamin P. Shaji replies:

The project includes camera, Raspberry Pi, Arduino Uno and modem. Collectively, it will cost you around ₹ 7000. Remaining parts or accessories depend on your requirement. Total maximum cost for this project would be about ₹ 12,000.

HVDC POWER SUPPLY

This is regarding 'HVDC Power Supply Design' DIY project published in February issue. Can I use it as an electric insect killer? What modifications are required to get 3000V DC output?

Rahmathullah

Through email

The author Ronie Adhiraaj Ghosh replies: For such high voltage output, limit output current to a very small value, otherwise it can be extremely dangerous. You need special tools to handle the circuit, as most electrical insulations are rated up to 600V.

Insect zapper circuits are based on transformer and voltage doubler circuits. This, however, is a clean high-voltage DC step-up circuit. For modifications, you may need high voltage sustaining transistors, diodes with peak inverse voltages greater than 3000V and capaci-

From electronicsforu.com

Electronics Projects

In 'Water Level Indicator' circuit available on <https://electronicsforu.com>, can I connect a buzzer to the circuit?

Rana Waseem

EFY. Yes, you can connect a buzzer across LED3 to give audio alerts when the water tank is full!

In 'Low-Cost LPG Leakage Detector' circuit available on <https://electronicsforu.com>, can I use a single comparator instead of a dual one? Why did you use a dual comparator here?

Umesh

EFY. You can use a single comparator IC. LM393 IC was used by the author because it is easily available in the market.

In 'Micro Inverter' circuit available on <https://electronicsforu.com>, what is the rating and type of the battery used?

Vivek Yadav

EFY. 12V, 7Ah rechargeable lead-acid battery was used during testing at EFY Lab.

tors with high voltage ratings. As some of these components may not be easily available in the market, you may use suitable voltage doubler circuits.

FACE DETECTION USING OPENCV

In 'Real-Time Face Recognition Using Python And OpenCV' DIY article published in April 2017 issue, the camera is not opening. I downloaded att_faces library for face_rec.py program. I can access the training, but the program closes automatically after some time. Please help!

Sayak

Through email

The author Aquib Javed Khan replies: You need to give more than two samples during training. There are no problems with the program. Please read the article again to understand the training process.