

NebuLink Node

Low cost and easy to use

modules for your IoT applications

SLS offers cost-effective, high volume wireless NebuLink Nodes that are easily integrated with the Internet of Things (IoT) applications. These Nodes are equipped with ultra-low power 32-bit RISC CPU with the clock speed of 1MHz – 32MHz and processor with 32 kB RAM and 512 kB flash memory on-board. Integrated with Zigbee Pro Stack and Nebulae 6LoWPAN Stack makes the NebuLink Nodes a versatile addition to any IoT solutions and are a great value for the money.

Low
cost
and
easy
to use




NLN 100a



NLN 100b



NLN 100c



NLN 100d



NLN 100e

Frequency Band	ISM 2.4 GHz	ISM 2.4 GHz	ISM 2.4 GHz	ISM 2.4 GHz	863.25MHz to 875.65MHz 902MHz to 928MHz (OPTIONAL)
Rx Sensitivity	-96 dBm	-96 dBm	-96 dBm	-106 dBm	-124 dBm
Security	128-bit AES	128-bit AES	128-bit AES	128-bit AES	128-bit AES
Antenna options	PCB Antenna, U.FL Connector, Wire Antenna	U.FL Connector	PCB Antenna, U.FL Connector, PCB Antenna or U.FL Connector	U.FL Connector	U.FL Connector

Contact us at +91 2692 232501 (ext. 47) or Write to us at sales@slscorp.com



For Documentation
Scan QR Code or visit
<http://www.slscorp.com/marcom.html>

NEBULAE
DESIGN TO CONNECT
nebulae.io

Powered By

