

ST25DV-PWM series



Dynamic NFC/RFID tag ICs ISO15693 NFC Forum type 5



ISO/IEC 15693 NFC Forum type 5 Dynamic Tag ICs with Pulse Width Modulation (PWM) outputs controlled by contactless interface

ST25DV02K-W product belongs to ST25 family. These dynamic NFC/RFID tag ICs offer a 13.56MHz long-range interface and PWM outputs.

It is compliant with ISO/IEC 15693 and NFC Forum Tag type 5 standards and embeds an EEPROM memory of 2 Kbits, which can be divided for use-case flexibility.

The PWM outputs can be programmed independently and securely, allowing a large field of application.

The IC provides live update of PWM parameters by contactless interface, extending the user experience.

KEY FEATURES

- Industry standard interfaces:
 - ISO15693 NFC Forum Type V
 - 13.56 MHz carrier frequency
 - 2-Kbit EEPROM configurable in 1 or 2 areas, each area is protected by password command:
 - 64-bit password 1 area.
 - 2x 32-bit password 2 areas
- Pulse width Modulation outputs
 - Up to 2x independent outputs
 - Up to 15-bit resolution
 - 62.5ns resolution step
- Power Supply: 1.8V to 5.5V
- -40°C to 105°C (PWM) temperature range
- TruST25 Digital Signature

KEY BENEFITS

- 2 in 1 chip, putting NFC connectivity with PWM functionality
- Cost optimized solution to address low end market
- Significant BOM reduction as no MCU is to drive the system

KEY APPLICATIONS

- NFC Analog Control
- Industrial application
- Lighting LED Driver
- Motor Control



STMicroelectronics Pvt Ltd

Plot No 1, Knowledge Park III,
Greater Noida 201308, Uttar Pradesh, India

Authorized distributors

• **Arrow:** Anurag: 9910645646 • **Asia Lucky:** Munish: 9717091771 • **Avnet:** Prakash: 9686671300
• **EDOM:** Om Prakash: 9910075895 • **Future:** Sunil: 9844640436 • **Nexty:** Priti: 9819794974
• **Teck:** Surendranath: 9810728299 • **WT:** Ramkumar: 9008088998 • **Yosun:** Amit: 9902509977

Send Enquiry to: nidhi-sehgal.kaul@st.com

www.st.com/st25