



FEEDBACK

YOUR SUGGESTIONS

THANK YOU!

I have been reading EFY for the last few months. I learn something new from every issue. EFY publishes a lot of valuable information about latest trends and development in electronics. Thank you!

I also like DIY section, and would like to try as many projects as possible. Recently, I constructed 'Wireless LCD Display Via Bluetooth' DIY project published in May issue. It is working well. Thank you for the project and the source code!

Marukurthi Sai

Rajahmundry (AP)

EFY. Thanks for the feedback!

MY SUGGESTIONS

I am a subscriber to EFY and an embedded engineer in the industrial Internet of Things (IIoT) space. The magazine carries very interesting and informative articles. I suggest you cover topics related to industrial Ethernet protocols like Profinet, Modbus and Profibus.

Adarsh. S.R.

Through email

EFY. Thanks for the feedback! We will try to publish these as soon as we receive suitable articles from our contributors.

IOT PROJECTS

Please share a list of published projects based on the IoT, related to electronics and communication systems.

Sarvani Tumuluri

Through email

EFY. The following are some IoT-based projects published in EFY:

1. Getting Started With NodeMCU Development Board For The IoT, November 2017
2. IoT-Smart Alert Notification Using Android App, March 2017
3. IoT-Based Smartcamera Using Android App And Raspberry Pi, November 2016
4. IoT Wi-Fi Temperature-Logging

System, March 2016

5. Introduction To Smart Wi-Fi, March 2016

EFY magazines is available at various online stores such as www.magzter.com and www.amazon.com

SOURCE CODE

'Temperature Monitoring On Smartphone' DIY article published in July issue does not have source code for .apk file. Please publish the entire source code for the project.

Sreejith. B.K.

Through email

EFY. The source code including .aia file for .apk file is available for free download at <http://efy.efymag.com/admin/issuepdf/Temperature%20monitoring%20on%20smartphone.rar>

LI-FI DONGLE

This is regarding 'Design Your Own Li-Fi Dongle And Speaker' DIY article published in July 2017 issue.

1. Which operational amplifier (op-amp) or integrated circuit (IC) is best suited for the construction of trans-impedance (transfer-impedance) amplifier with two female USB ports: one for solar panel photodetector and one that feeds the computer system for Li-Fi Internet receiver dongle?

2. Is it possible to use two op-amps: one for initial voltage boost and the other for final voltage boost to increase the desired Internet speed?

3. Please describe the relationship of byte/second between these parameters. Does bit/second depend on data logging of the computer motherboard on receiving the incoming amplified signal? Kindly explain.

Ololo chukwuemeka

Through email

The author Dr J. Manikandan replies:

Thanks for showing interest in the article! I believe you are trying to work on Li-Fi Internet connectivity, whereas this project is based on Li-Fi transmission of

audio signals. However, I have tried to answer your queries as given below:

1. If you want to transmit data on Li-Fi-based Internet, the entire test setup will change. I recommend that you use a high-speed photodetector with trans-impedance amplifier that best suits your Internet data rate. We focused on transmission of audio signals using Li-Fi, and the solar panel employed was able to detect variations in light caused due to audio signals.

2. Use of op-amps will not help in increasing the speed of the Internet. Also, it is not clear why you want to do so. If you want to boost the voltage on the receiver side, to receive Li-Fi transmitted data, I suggest you use a high-speed photodetector and corresponding trans-impedance amplifier.

3. A computer expert will be able to answer this question better.

AUDIO AMPLIFIER

In '3W/6W Audio Amplifier Using TDA2003' DIY article published in June 2017 issue, I have the following queries:

1. According to datasheet of TDA2003, the IC can output 10W on a 2-ohm load and about 5.5W on a 4-ohm load. But, in the circuit, an 8-ohm loudspeaker is used. What is the actual output we can get from TDA2003 IC?

2. Operating voltage is 6V or 12 V, 500 mA. If we use an unregulated 12V adaptor, voltage may exceed to around 18V. Will it affect the circuit in any way?

3. What is the maximum output we can get by varying the gain at any given load, say, 4-ohm in this circuit?

Anirvan Kule

Kolkata

The author Raj K. Gorkhali replies:

Thank you for your interest in the article!

1. You can get 3W output on a 8-ohm, 6W speaker using 6V DC (500mA) power supply and 6W output using 12V DC (500mA) power supply.

2. Operating supply voltage for the amplifier should not exceed 18V.

3. We can get maximum output power between 6W and 12W on a 4-ohm load.