



Bringing the power of IoT in Medical Industry

We at SLS offer a series of wireless NebuLink Nodes which can easily convert Medical Devices into Connected IoT devices to manage wellness. These nodes are equipped with ultra-low power 32-bit RISC CPU with the clock speed upto 32MHz with 32 kB RAM, 512 kB flash and 4kB EEPROM providing AES 128 bit encrypted security.

**Low
cost
and
easy
to use**

	 NLN 100a STARTING FROM INR 399	 NLN 100b INR 499	 NLN 100c STARTING FROM INR 430	 NLN 100d INR 699	 NLN 100e INR 1190
Frequency Band	ISM 2.4 GHz	ISM 2.4 GHz	ISM 2.4 GHz	ISM 2.4 GHz	863.25MHz to 875.65MHz 902MHz to 928MHz (OPTIONAL)
Tx Current Consumption	28.8mA@ +10dBm; 19.6mA@ +8.5dBm; 14mA @ +3dBm	28.8mA@ +10dBm; 19.6mA@ +8.5dBm; 14mA @ +3dBm	26.8mA@ +10dBm; 19.6mA@ +8.5dBm; 14mA @ +3dBm	104mA@ +19.88dBm	9mA@ +0dBm, 29mA@ +14dBm
Rx Current Consumption	19.6mA@ +10dBm; 13mA@ 0dBm	19.2mA@ +10dBm; 13mA@ 0dBm	19.6mA@ +10dBm; 13mA@ 0dBm	26mA@ +19.88dBm	11mA
Digital IO	Up to 5	Up to 20	Up to 20	Up to 20	Up to 20
Antenna options	PCB Antenna, U.FL Connector, Wire Antenna	U.FL Connector	PCB Antenna, U.FL Connector, PCB Antenna or U.FL Connector	U.FL Connector	U.FL Connector

*TAXES AS APPLICABLE

Contact us at +91 2692 232501(ext. 47) or Email us at sales@nebulae.io



For more information
scan QR Code or visit
www.nebulae.io

NEBULAE
DESIGN TO CONNECT

Powered By

