



COMPONENTS

LED drivers

Designers of high-performance automotive lighting applications now have a simpler, more efficient method for driving high-brightness LEDs (HBLEDs) with MAX25610A and MAX25610B LED drivers from Maxim Integrated Products. The synchronous buck, buck-boost LED drivers/DC-DC converters offer a complete solution that features industry-leading EMI performance, without compromising on efficiency and size. These ICs drive up to eight HBLEDs directly from the automotive battery and integrate many external components to save on bill of materials (BOM) costs and space, making these excellent solutions for automotive lighting systems as well as industrial and commercial lighting applications.

Maxim Integrated Products Inc.
www.maximintegrated.com

Switching regulator

Texas Instruments has introduced an ultra-low-power switching regulator with an operating quiescent current (IQ) at 60 nA. TPS62840 synchronous step-down converter delivers very high light-load efficiency of eighty per cent at 1µA load, which can enable designers to extend the battery life of their systems, or use fewer or smaller batteries to shrink their overall power supply solution size and reduce cost.

Additionally, the new DC/DC converter's wide input voltage (VIN) range of 1.8V to 6.5V supports a variety of battery chemistries and configurations.

Texas Instruments
www.ti.com

Clock buffers

As data centres migrate to greater bandwidth and faster infrastructure, the need

for higher performance timing devices becomes critical. Four new 20-output differential clock buffers that exceed PCIe Gen 5 jitter standards for next-generation data centre applications are now available from Microchip Technology. ZL40292 (85Ω termination) and ZL40293 (100Ω termination) are specifically designed to meet DB2000Q specification, while ZL40294 (85Ω termination) and ZL40295 (100Ω termination) are designed to meet DB2000QL industry standard.

Microchip Technology Inc.
www.microchip.com

LED driver IC

Infineon Technologies has introduced the new LED driver IC ILD8150/E. It features an innovative hybrid dimming mode technology for achieving 0.5 per cent target current. With its supply voltage range from 8V DC up to 80V DC, the driver IC provides a high safety voltage margin for applications operating close to safe extra-low voltage (SELV) limits. The driver IC is ideally suited for general and professional LED lighting applications with high dimming requirements.

Infineon Technologies India Pvt Ltd
www.infineon.com

Wheel speed sensor

Allegro MicroSystems has released its latest wheel speed sensor product line, which meets all the industry's requirements from high accuracy GMR to back-biased Hall-effect sensor solutions. A19250 and A19350 are built on Allegro's patented GMR technology that achieves industry-leading performance and is orientation-compatible as a drop-in solution to Hall-effect.

The A19250 and A19350 GMR-based ICs are designed for use in conjunction with magnet encoder rings to measure speed and direction information.

Allegro MicroSystems
www.allegromicro.com

Power supply monitoring IC

ROHM Semiconductors has announced the availability of a power supply monitoring IC, BD39040MUF-C, with BIST (built-in self-test) that supports functional safety.

This IC is ideal for automotive application power supply systems requiring fail-safe measures such as electric power steering as well as sensors and cameras for autonomous driving and ADAS.

ROHM Semiconductor India Pvt Ltd
www.rohm.com

Spring-loaded LVDTs

NewTek's gage head linear variable differential transformers (LVDTs) are ideal for industrial environments requiring a reliable and rugged sensor. With near infinite resolution and excellent repeatability, these spring-loaded LVDTs are



ideal for quality testing and gaging with several customisation options available. Gage heads are available as AC LVDTs, voltage output DC LVDTs or 4-20 mA current output LVDTs.

NewTek Sensor Solutions
www.newteksensors.com

Gate driver

SCALE-iFlex gate driver family consists of a central isolated master control (IMC) 2SI0400T2xxC and up to