

four module adapted gate drivers (MAGs) 2SM0120D2xxC together with a cable set. The IMC is designed for operation of power modules with a blocking voltage of up to 3300V, whereas MAGs



Isolated Master Control

Module Adapted Gate Driver

are available in variants optimised for power modules from different suppliers and with various device technologies in 3300V voltage class.

Power Integrations
www.power.com

TEST & MEASUREMENT

Base station simulator

Anritsu has announced the release of its new Log Import Option to strengthen IMS evaluation functions of the company's base station simulator MD8475B.



Using this solution, live-network Wireshark logs are converted automatically to IMS scripts for easy configuration of an automated test environment to replay VoLTE/IMS faults when used together with IMS Basic Script option.

Anritsu India Pvt Ltd
www.anritsu.com

Clamp meter

The MA440 series meters are fully loaded with multimeter functions and built-in non-contact voltage (NCV) detector to meet all application needs. Key features are:

- True RMS feature for accurate readings regardless of waveforms
- Large backlit LCD display and built-in flashlight



- NCV, AC/DC voltage, AC/DC current, resistance, capacitance, frequency, type-k temperature, diode test, continuity
- Relative mode for capacitance, DC zero and offset adjustment, data hold, maximum/minimum, auto power off and low battery indicator

FLIR Systems India Pvt Ltd
www.flir.in

Production tester

Rohde & Schwarz and Marvin Test Solutions have cooperated to create a unique turnkey solution suited for beamforming integrated circuits (IC) used in 5G mmWave (FR2) and satellite communications. The resulting



production tester TS 900e-5G from Marvin Test Solutions is based on the new R&S ZNBT40 multiport vector network analyser (VNA).

Rohde & Schwarz GmbH & Co. KG
www.rohde-schwarz.com

DC electronic load

SDL1000X/SDL1000X-E series programmable DC electronic load has



a user-friendly interface and superb performance specifications. SDL1020X/SDL1020X-E models feature an input range of 150V/30A 200W, while SDL1030X/SDL1030X-E have an input range of 150V/30A 300W.

SDL1000X series leads with a measurement resolution of 0.1mV/0.1mA, and base SDL1000X-E series' resolution is 1mV/1mA and adjustable current rise times from 0.001A/μs ~ 2.5A/μs.

For remote communication and control, the SDL series includes RS232/USB/LAN interface types. SDL1000X series delivers stability over a wide range of applications and can meet all kinds of testing requirements.

Siglent Technologies Co. Ltd
www.siglent.com

Evaluation kits

TDK has launched two evaluation kits that provide an initial impression of varied possibilities of haptic feedback that can be realised with PowerHap piezo actuators.

BOS1901-Kit development kit is designed for and includes three 60V actuators. Main features of BOS1901 piezoelectric driver are its small dimensions, low current consumption and fast response times.

The second evaluation kit is suitable not only for 60V PowerHap types, but



also 120V types, and is available in two versions: driver for one actuator and driver for up to five actuators. These kits likewise contain three types of PowerHap actuators.

TDK Corp.
www.tdk-electronics.tdk.com

POWER SUPPLY

Power supplies

Traco Power has released its TIB 480-EX family of 480-watt DIN rail power supplies that are



designed for harsh environments and hazardous locations with certifications for ATEX II3G

and UL HazLoc Class I/Div 2 standards.

These products bring a new performance level to industrial applications;